



Electric Automation
Automation specialists

Reference: RBR 101 AR-24VAC/D
Code: 1SNA645519R0600

RBR101AR-24VAC/DC Interface relay
R600 1n/c+RC,A1-A2=24VAC/
DC,250V/10mA-6A,LED

Buy it at Electric Automation Network



Spring relay with contact protection RBR101AR 24vac/dc : 24vac-dc input / 1NC 10 mA upto 6A with led

Ordering

EAN:	4013614508301
Minimum Order Quantity:	5 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	12 mm
Product Net Height:	67.5 mm
Product Net Depth:	75 mm
Product Net Weight:	0.04 kg

Container Information

Package Level 1 Units:	5 piece
Package Level 1 Width:	73 mm
Package Level 1 Height:	71 mm
Package Level 1 Length:	80 mm
Package Level 1 Gross Weight:	0.24 kg

Package Level 1 EAN:	3472596455194
----------------------	---------------

Technical

Function:	Boxed interface relay R600
Sub-Function:	Relay with built in LED and RC circuit
Output:	1 n/c contact
Output Signal:	12 ... 250 V AC / 10 mA ... 6 A
Rated Control Supply Voltage (U _s):	24 V AC/DC
Terminal Type:	Spring Terminals

Certificates and Declarations (Document Number)

CSA Certificate:	CSA_254821
cUR Certificate:	cUR_E352056
Declaration of Conformity - CE:	1SND225050C1000
EAC Certificate:	EAC_RU_C-FR.ME77.B.01634
LR Certificate:	LRS_0620042
UR Certificate:	UR_E352056

Classifications

Object Classification Code:	K
ETIM 4:	EC001437 - Switching relay
ETIM 5:	EC001437 - Switching relay
UNSPSC:	39121500
eClass:	7.0 27371601