



Electric Automation
Automation specialists

Reference: OBROA 2000-24VAC/D
Code: 1SNA645529R0000

OBROA2000-24VDC Optocoupler R600
2A,A1-A2=24VDC, Triac

Buy it at [Electric Automation Network](#)



Spring optocoupler OBROA2000 24vac/dc : 24vdc input / 10 upto 230vac output 2A

Ordering

EAN:	4013614508394
Minimum Order Quantity:	5 piece
Customs Tariff Number:	85369085

Dimensions

Product Net Width:	12 mm
Product Net Height:	67.5 mm
Product Net Depth:	75 mm
Product Net Weight:	0.04 kg

Container Information

Package Level 1 Units:	5 piece
Package Level 1 Width:	73 mm
Package Level 1 Height:	71 mm
Package Level 1 Length:	80 mm
Package Level 1 Gross Weight:	0.24 kg

Package Level 1 EAN:	3472596455293
----------------------	---------------

Technical

Function:	Boxed optocoupler R600
Output:	solid-state output
Output Signal:	10 ... 230 V AC / 25 mA ... 2 A
Rated Control Supply Voltage (U _s):	24 V AC/DC
Terminal Type:	Spring Terminals

Certificates and Declarations (Document Number)

CSA Certificate:	CSA_254821
cUR Certificate:	cUR_E352056
Declaration of Conformity - CE:	1SND225053C1000
EAC Certificate:	EAC_RU_C-FR.ME77.B.01634
LR Certificate:	LRS_0620042
UR Certificate:	UR_E352056

Classifications

Object Classification Code:	K
ETIM 4:	EC001504 - Optocoupler
ETIM 5:	EC001504 - Optocoupler
UNSPSC:	43172000
eClass:	7.0 27371604