



Electric Automation
Automation specialists

Reference: Módulo relé CR-S04
Code: 1SVR405501R4010

CR-S048VDC1R Interface relay 1c/o, A1-
A2=48VDC, Output=6A/250VAC

[Buy it at Electric Automation Network](#)



CR-S048VDC1R Interface relay 1c/o, A1-A2=48VDC, Output=6A/250VAC

Ordering

EAN:	4013614499142
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	5 mm
Product Net Height:	15 mm
Product Net Depth:	28 mm
Product Net Weight:	0.005 kg

Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	300 mm
Package Level 1 Height:	23.7 mm
Package Level 1 Length:	7.4 mm
Package Level 1 Gross Weight:	0.06 kg

Package Level 1 EAN:	4013614486470
----------------------	---------------

Technical

Function:	Pluggable slim interface relay CR-S
Sub-Function:	Relay with standard contacts
Output:	1 c/o (SPDT) contact
Output Signal:	250 V / 6 A
Rated Control Supply Voltage (U _s):	48 V DC

Environmental

Ambient Air Temperature:	Operation -40 ... +85 °C Storage 0 ... +40 °C
RoHS Status:	Following EU Directive 2011/65/EC

Certificates and Declarations (Document Number)

CQC Certificate:	CQC_14002108002
CSA Certificate:	CSA_262671-2785865
cUR Certificate:	cUR_E244330
Declaration of Conformity - CE:	1SAD938500-0218
EAC Certificate:	EAC_RU_C-PL.ME77.B.01873
RoHS Information:	1SAA981068-4401
UR Certificate:	UR_E244330
VDE Certificate:	VDE_40039479

Classifications

Object Classification Code:	K
ETIM 4:	EC001437 - Switching relay
ETIM 5:	EC001437 - Switching relay
eClass:	7.0 27371601