



**Electric Automation**  
Automation specialists

Reference: Base CR-S220/240VA  
Code: 1SVR405521R7200

CR-S220/240VADC1SZ Socket 1c/o, A1-  
A2=220-240VAC/DC, 250VAC

[Buy it at Electric Automation Network](#)



CR-S220/240VADC1SZ Socket 1c/o, A1-A2=220-240VAC/DC, 250VAC spring terminals

## Ordering

EAN:	4013614499272
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85369010

## Dimensions

Product Net Width:	6.2 mm
Product Net Height:	76.6 mm
Product Net Depth:	94.7 mm
Product Net Weight:	0.025 kg

## Container Information

Package Level 1 Units:	10 piece
Package Level 1 Width:	93 mm
Package Level 1 Height:	81 mm
Package Level 1 Length:	66 mm
Package Level 1 Gross Weight:	0.26 kg

Package Level 1 EAN:	4013614486401
----------------------	---------------

## Technical

Function:	Accessory for interface relays CR-S
Sub-Function:	Socket
Rated Control Supply Voltage (U <sub>s</sub> ):	220 ... 240 V AC/DC
Terminal Type:	Spring Terminals

## Environmental

Ambient Air Temperature:	Operation -40 ... +55 °C Storage 0 ... +40 °C
RoHS Status:	Following EU Directive 2011/65/EC

## Technical UL/CSA

Connecting Capacity UL/CSA:	Flexible 14 AWG Rigid 14 AWG
Tightening Torque UL/CSA:	4.42 in·lb

## Certificates and Declarations (Document Number)

CSA Certificate:	CSA_262671-2785566
cUR Certificate:	cUR_E244328
Declaration of Conformity - CE:	1SAD938500-0218
EAC Certificate:	EAC_RU_C-PL.ME77.B.01873
RoHS Information:	1SAA981068-4401
UR Certificate:	UR_E244328

## Classifications

Object Classification Code:	K
ETIM 4:	EC001456 - Relay socket
ETIM 5:	EC001456 - Relay socket
eClass:	7.0 27371603