



Electric Automation
Automation specialists

Reference: CR-U110AC2L
Code: 1SVR405621R7100

CR-U110AC2L Pluggable interface relay
2c/o, A1-A2=110VAC, 250V/10A, LED

Buy it at [Electric Automation Network](#)



The CR-U110AC2L pluggable interface relay is from the CR-U (universal) relay range. This relay operates with a 110 V AC rated control supply voltage and has 2 c/o (SPDT) output contacts rated at 250 V / 10 A. The relay has an integrated orange test button for manual actuation and locking of the output contacts and an integrated LED. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories.

Ordering

EAN:	4013614498503
Minimum Order Quantity:	10 piece
Customs Tariff Number:	85364900

Dimensions

Product Net Width:	35 mm
Product Net Height:	54.4 mm
Product Net Depth:	35 mm
Product Net Weight:	0.083 kg

Container Information

Package Level 1 Units:	10 piece
------------------------	----------

Package Level 1 Width:	182 mm
Package Level 1 Height:	76 mm
Package Level 1 Length:	77 mm
Package Level 1 Gross Weight:	0.87 kg
Package Level 1 EAN:	4013614374135

Technical

Function:	Pluggable universal interface relay CR-U
Sub-Function:	Relay with built in LED
Output:	2 c/o (SPDT) contacts
Output Signal:	250 V / 10 A
Rated Control Supply Voltage (U _s):	110 V AC

Environmental

RoHS Status:	Following EU Directive 2011/65/EC
--------------	-----------------------------------

Certificates and Declarations (Document Number)

CCC Certificate:	CCC_2012010303554029
CSA Certificate:	CSA_1587291
Declaration of Conformity - CE:	1SAD938501-0159
EAC Certificate:	EAC_RU_C-PL.ME77.B.01873
GOST Certificate:	GOST_POCC_DE.AB76.D02256
LR Certificate:	LR_05_20002_E3
RMRS Certificate:	RMRS_12.04008.250
RoHS Information:	1SAA981040-4404
UR Certificate:	UR_E244330
VDE Certificate:	VDE_40019116

Classifications

Object Classification Code:	K
ETIM 4:	EC001437 - Switching relay
ETIM 5:	EC001437 - Switching relay
UNSPSC:	39121500
eClass:	7.0 27371601