



Electric Automation
Automation specialists

Reference: CR-U110DC2L
Code: 1SVR405621R8100

CR-U110DC2L Pluggable interface relay
2c/o, A1-A2=110VDC, 250V/10A, LED

Buy it at [Electric Automation Network](#)



The CR-U110DC2L pluggable interface relay is from the CR-U (universal) relay range. This relay operates with a 110 V DC rated control supply voltage and has 2 c/o (SPDT) output contacts rated at 250 V / 10 A. The relay has an integrated blue test button for manual actuation and locking of the output contacts and an integrated LED. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories.

Ordering

| | |
|-------------------------|---------------|
| EAN: | 4013614498527 |
| Minimum Order Quantity: | 10 piece |
| Customs Tariff Number: | 85364900 |

Dimensions

| | |
|---------------------|----------|
| Product Net Width: | 35 mm |
| Product Net Height: | 54.4 mm |
| Product Net Depth: | 35 mm |
| Product Net Weight: | 0.083 kg |

Container Information

| | |
|------------------------|----------|
| Package Level 1 Units: | 10 piece |
|------------------------|----------|

| | |
|-------------------------------|---------------|
| Package Level 1 Width: | 182 mm |
| Package Level 1 Height: | 76 mm |
| Package Level 1 Length: | 77 mm |
| Package Level 1 Gross Weight: | 0.87 kg |
| Package Level 1 EAN: | 4013614374142 |

Technical

| | |
|---|--|
| Function: | Pluggable universal interface relay CR-U |
| Sub-Function: | Relay with built in LED |
| Output: | 2 c/o (SPDT) contacts |
| Output Signal: | 250 V / 10 A |
| Rated Control Supply Voltage (U _s): | 110 V DC |

Environmental

| | |
|--------------|-----------------------------------|
| RoHS Status: | Following EU Directive 2011/65/EC |
|--------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|---------------------------------|--------------------------|
| CCC Certificate: | CCC_2012010303554029 |
| CSA Certificate: | CSA_1587291 |
| Declaration of Conformity - CE: | 1SAD938501-0159 |
| EAC Certificate: | EAC_RU_C-PL.ME77.B.01873 |
| GOST Certificate: | GOST_POCC_DE.AB76.D02256 |
| LR Certificate: | LR_05_20002_E3 |
| RMRS Certificate: | RMRS_12.04008.250 |
| RoHS Information: | 1SAA981040-4404 |
| UR Certificate: | UR_E244330 |
| VDE Certificate: | VDE_40019116 |

Classifications

| | |
|-----------------------------|----------------------------|
| Object Classification Code: | K |
| ETIM 4: | EC001437 - Switching relay |
| ETIM 5: | EC001437 - Switching relay |
| UNSPSC: | 39121500 |
| eClass: | 7.0 27371601 |