



**Electric Automation**  
Automation specialists

Reference: CR-U220DC3  
Code: 1SVR405622R9000

CR-U220DC3 Pluggable interface relay  
3c/o, A1-A2=220VDC, 250V/10A

Buy it at [Electric Automation Network](#)



The CR-U220DC3 pluggable interface relay is from the CR-U (universal) relay range. This relay operates with a 220 V DC rated control supply voltage and has 3 c/o (SPDT) output contacts rated at 250 V / 10 A. The relay has an integrated blue test button for manual actuation and locking of the output contacts. Standard sockets, pluggable function modules, holder and marker are available as accessories.

### Ordering

|                         |               |
|-------------------------|---------------|
| EAN:                    | 4013614498756 |
| Minimum Order Quantity: | 10 piece      |
| Customs Tariff Number:  | 85364900      |

### Dimensions

|                     |          |
|---------------------|----------|
| Product Net Width:  | 35 mm    |
| Product Net Height: | 54.4 mm  |
| Product Net Depth:  | 35 mm    |
| Product Net Weight: | 0.083 kg |

### Container Information

|                        |          |
|------------------------|----------|
| Package Level 1 Units: | 10 piece |
| Package Level 1 Width: | 182 mm   |

|                               |               |
|-------------------------------|---------------|
| Package Level 1 Height:       | 76 mm         |
| Package Level 1 Length:       | 77 mm         |
| Package Level 1 Gross Weight: | 0.87 kg       |
| Package Level 1 EAN:          | 4013614375712 |

## Technical

|   |  |
|---|--|
| Function:                                       | Pluggable universal interface relay CR-U |
| Sub-Function:                                   | Relay w/o built in LED                   |
| Output:   | 3 c/o (SPDT) contacts                    |
| Output Signal:                                  | 250 V / 10 A                             |
| Rated Control Supply Voltage (U <sub>s</sub> ): | 220 V DC                                 |

## Environmental

|              |                                   |
|--------------|-----------------------------------|
| RoHS Status: | Following EU Directive 2011/65/EC |
|--------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                 |                          |
|---------------------------------|--------------------------|
| CCC Certificate:                | CCC_2012010303554029     |
| CSA Certificate:                | CSA_1587291              |
| Declaration of Conformity - CE: | 1SAD938501-0159          |
| EAC Certificate:                | EAC_RU_C-PL.ME77.B.01873 |
| GOST Certificate:               | GOST_POCC_DE.AB76.D02256 |
| LR Certificate:                 | LR_05_20002_E3           |
| RMRS Certificate:               | RMRS_12.04008.250        |
| RoHS Information:               | 1SAA981040-4404          |
| UR Certificate:                 | UR_E244330               |
| VDE Certificate:                | VDE_40019116             |

## Classifications

|                             |                            |
|-----------------------------|----------------------------|
| Object Classification Code: | K                          |
| ETIM 4:                     | EC001437 - Switching relay |
| ETIM 5:                     | EC001437 - Switching relay |
| UNSPSC:                     | 39121500                   |
| eClass:                     | 7.0 27371601               |