



**Electric Automation**  
Automation specialists

Reference: CL-LDC.LDC2  
Code: 1SVR440821R0000

CL-LDC.LDC2 Display base module  
24VDC

[Buy it at Electric Automation Network](#)



The CL-LDC.LDC2 is a display base module from the CL range. The display base module is a CPU and power supply and operates with an input voltage of 24 V DC. It offers the possibility of connecting local and remote expansions via CL-LINK. 256 rungs with 4 contacts in series plus 1 coil can be programmed. The following functions are available: 32 freely editable display texts, 32 week and 32 year timers, 1 set cycle time, 32 multifunction timing relays, 4 operating hours counters, 16 analog value comparators, threshold value switches, 4 high-speed counters, 4 frequency counters, 2 incremental counters and various memory functions, text functions, value entry functions and value display functions.

### Ordering

EAN:	4013614389825
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389099

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	122 mm
Package Level 1 Height:	35 mm
Package Level 1 Length:	94 mm
Package Level 1 Gross Weight:	0.184 kg

### Dimensions

Product Net Width:	107.5 mm
Product Net Depth:	30 mm
Product Net Height:	90 mm
Product Net Weight:	0.164 kg

## Technical

Function:	Display system
Sub-Function:	Display base module
Rated Operational Voltage:	24 V DC

## Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

## Certificates and Declarations (Document Number)

CSA Certificate:	CSA_1875990
Declaration of Conformity - CE:	1SAD938500-0233
GL Certificate:	GL_44544-07HH
GOST Certificate:	GOST_0197271
LR Certificate:	LR_07_20019
RoHS Information:	1SAA981046-4401
UL Certificate:	UL_E179811

## Classifications

Object Classification Code:	K
ETIM 4:	EC001417 - Logic module
ETIM 5:	EC001417 - Logic module
eClass:	7.0 27242216
UNSPSC:	43172000