



Electric Automation
Automation specialists

Reference: CL-LDC.LAC2
Code: 1SVR440823R0000

CL-LDC.LAC2 Display base module
110...240VAC

Buy it at [Electric Automation Network](#)



The CL-LDC.LAC2 is a display base module from the CL range. The display base module is a CPU and power supply and operates with an input voltage of 100-240 V AC. It offers the possibility of connecting local and remote expansions via CL-LINK. 256 rungs with 4 contacts in series plus 1 coil can be programmed. The following functions are available: 32 freely editable display texts, 32 week and 32 year timers, 1 set cycle time, 32 multifunction timing relays, 4 operating hours counters, 16 analog value comparators, threshold value switches, 4 high-speed counters, 4 frequency counters, 2 incremental counters and various memory functions, text functions, value entry functions and value display functions.

Ordering

EAN:	4013614390142
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362010

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	122 mm
Package Level 1 Height:	35 mm
Package Level 1 Length:	94 mm
Package Level 1 Gross Weight:	0.184 kg

Dimensions

Product Net Width:	107.5 mm
Product Net Depth:	30 mm
Product Net Height:	90 mm
Product Net Weight:	0.164 kg

Technical

Function:	Display system
Sub-Function:	Display base module
Rated Operational Voltage:	110 ... 240 V AC

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Certificates and Declarations (Document Number)

CSA Certificate:	CSA_1875990
Declaration of Conformity - CE:	1SAD938500-0234
GL Certificate:	GL_44544-07HH
GOST Certificate:	GOST_0197271
LR Certificate:	LR_07_20019
RoHS Information:	1SAA981046-4401
UL Certificate:	UL_E179811

Classifications

Object Classification Code:	K
ETIM 4:	EC001417 - Logic module
ETIM 5:	EC001417 - Logic module
eClass:	7.0 27242216
UNSPSC:	43172000