



Electric Automation
Automation specialists

Reference: ZLS905E20-3LNLALB
Code: 2CCA183163R0001

ZLS905E20-3LNLALB Starter pack Touch proof with 20
Modules 3LNLALB

[Buy it at Electric Automation Network](#)



Starter pack Touch proof with 20 Modules L1,L2,L3 N LA,LB Pluggable socket system is completely fingersafe (IP2XB) together with the socket end piece

Ordering

EAN:	7612271417215
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389030

Dimensions

Product Net Width:	90 mm
Product Net Height:	28.5 mm
Product Net Depth:	394.2 mm
Product Net Weight:	0.753 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	132 mm
Package Level 1 Height:	67 mm
Package Level 1 Length:	404 mm
Package Level 1 Gross Weight:	0.949 kg

Package Level 1 EAN:	7612271417215
----------------------	---------------

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Additional Information

Product Main Type:	Accessories for Plug-in Distribution Systems
Product Name:	Accessories for Plug-in Distribution Systems
Rated Operational Voltage:	690 V AC 1000 V DC
Standards:	EN 60439-1, EN60439-2

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CCC451059C0202
Declaration of Conformity - CE:	2CCC451023D0601
RoHS Information:	2CCC451021D0201

Classifications

ETIM 4:	EC001522 - Busbar
ETIM 5:	EC001522 - Busbar
Object Classification Code:	W