



**Electric Automation**  
Automation specialists

Reference: F404A-K63/0.03

Code: 2CCF544310E0630

F404A-K63/0,03 Residual current operated circuit breaker 4 Poles 63A ~230/400V

Buy it at Electric Automation Network



F404A-K63/0,03 Residual current operated circuit breaker 4 Poles 63A - ~230/400V

## Ordering

EAN:	7612270104345
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362020

## Dimensions

Product Net Width:	72 mm
Product Net Height:	91 mm
Product Net Length:	72 mm
Product Net Depth:	75 mm
Product Net Weight:	0.430 kg

## Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	100 mm
Package Level 1 Height:	90 mm
Package Level 1 Length:	75 mm
Package Level 1 Gross Weight:	0.058 kg
Package Level 1 EAN:	7612270104345

## Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

## Additional Information

Frequency ( $f$ ):	50 ... 60 Hz
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	4
Power Loss:	3.2 W
Product Main Type:	F404
Product Name:	F404
Rated Current ( $I_n$ ):	63 A
Rated Operational Current ( $I_e$ ):	63 A
Rated Operational Voltage:	230 / 400 V AC
Rated Residual Current:	0.03_AMPx
Rated Voltage ( $U_r$ ):	230 / 400 V
Standards:	EN61008-1
Tripping Characteristic:	K

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CCC451059C0202
Declaration of Conformity - CE:	2CCY451110D0601
RoHS Information:	2CCC451021D0201

## Classifications

ETIM 4:	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 5:	EC002297 - Residual current circuit breaker (RCCB) module
Object Classification Code:	FB