



Electric Automation
Automation specialists

Reference: F402A-K40/0.03
Code: 2CCF552310E0400

F402A-K40/0,03 Residual Current Device
2 Poles 40A - ~230/400V

Buy it at [Electric Automation Network](#)



F402A-K40/0,03 Residual Current Device 2 Poles 40A - ~230/400V

Ordering

EAN:	7612270104482
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363020

Dimensions

Product Net Width:	91 mm
Product Net Height:	91 mm
Product Net Length:	72 mm
Product Net Depth:	72 mm
Product Net Weight:	0.25 kg

Container Information

Package Level 1 Units:	2 piece
Package Level 1 Width:	101 mm
Package Level 1 Height:	89 mm
Package Level 1 Length:	76 mm

Package Level 1 Gross Weight:	0.56 kg
Package Level 1 EAN:	7612270104482

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Additional Information

Frequency (f):	50 ... 60 Hz
IIT Publishing Status:	Level 0 - Information enabled
Power Loss:	9.3 W
Product Main Type:	F402
Product Name:	F402
Rated Current (I_n):	40 A
Rated Operational Current (I_e):	40 A
Rated Operational Voltage:	230 / 400 V AC
Rated Residual Current:	0.03 AMPx
Rated Voltage (U_r):	230 / 400 V
Standards:	EN61008-1
Tripping Characteristic:	K

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CCC451059C0202
Declaration of Conformity - CE:	2CCY451110D0601
RoHS Information:	2CCC451021D0201

Classifications

ETIM 4:	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 5:	EC002297 - Residual current circuit breaker (RCCB) module
Object Classification Code:	FB