



Electric Automation
Automation specialists

Reference: S401M-K25NP
Code: 2CCS571103R8517

S401M-K25NP Miniature Circuit Breaker
2 Pole NPK 25A 10000 ~230/400V

Buy it at Electric Automation Network



S401M-K25NP Miniature Circuit Breaker 2 Pole NPK 25A 10000 ~230/400V

Ordering

EAN:	7612270103737
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362020

Dimensions

Product Net Width:	36 mm
Product Net Height:	91 mm
Product Net Length:	82 mm
Product Net Depth:	75 mm
Product Net Weight:	0.235 kg

Container Information

Package Level 1 Units:	5 piece
Package Level 1 Width:	100 mm
Package Level 1 Height:	125 mm
Package Level 1 Length:	185 mm
Package Level 1 Gross Weight:	0.138 kg
Package Level 1 EAN:	7612270103737

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Additional Information

Frequency (f):	50 ... 60 Hz
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	2
Power Loss:	6.6 W
Product Main Type:	S402
Product Name:	S402
Rated Current (I_n):	25 A
Rated Operational Current (I_e):	25 A
Rated Operational Voltage:	230 / 400 V AC
Rated Short-Circuit Capacity (I_{cn}):	10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	10 kA
Rated Voltage (U_r):	230 / 400 V
Standards:	EN60898-1, EN60947-2
Tripping Characteristic:	K

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CCC451059C0202
Declaration of Conformity - CE:	2CCY451110D0601
RoHS Information:	2CCC413008D0201

Classifications

ETIM 4:	EC000042 - Miniature circuit breaker (MCB)
ETIM 5:	EC000042 - Miniature circuit breaker (MCB)
Object Classification Code:	FC