



Electric Automation
Automation specialists

Reference: S803-BB250
Code: 2CCS800900R0071

S803-BB250 Busbar

Buy it at Electric Automation Network



The S803-BB250 is a 3-pole busbar with 24 terminal lugs. It can be used for rated current up to 250A.

Ordering

EAN:	7612271208288
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85389030

Dimensions

Product Net Width:	651 mm
Product Net Height:	73.25 mm
Product Net Depth:	27 mm
Product Net Weight:	1.5 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	105 mm
Package Level 1 Height:	66 mm
Package Level 1 Length:	100 mm
Package Level 1 Gross Weight:	1.8 kg
Package Level 1 EAN:	7612271208288
Package Level 2 Units:	1

Environmental

Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +70 °C
--------------------------	--

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
--------------	---

Additional Information

Degree of Protection:	acc. to IEC 60529 IP20
Housing Material:	Insulation group I
IIT Publishing Status:	Level 0 - Information enabled
Product Main Type:	Accessories for High Performance Circuit Breakers HPCBs
Product Name:	Accessories for High Performance Circuit Breakers HPCBs
Rated Frequency (f):	50 / 60 Hz
Rated Insulation Voltage (U _i):	690 V AC
Rated Operational Current (I _e):	250 A
Rated Operational Voltage:	400/690 V AC
Recommended Screw Driver:	Pozidriv 2
Standards:	IEC 60439-2
Terminal Type:	Screw Terminals
Tightening Torque:	3.5 N·m

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CCC413003C0203
Declaration of Conformity - CE:	2CCC413003C0201
RoHS Information:	2CCC413008D0204

Classifications

E-nummer:	2101650
ETIM 4:	EC001522 - Busbar
ETIM 5:	EC001522 - Busbar
Object Classification Code:	F