



Electric Automation
Automation specialists

Reference: F204AS-40/0,5
Code: 2CSF204201R4400

F204 A S-40/0,5 Residual Current Dev.

Buy it at Electric Automation Network



The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications.

Ordering

EAN:	8012542784906
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363030

Dimensions

Product Net Width:	0.070 m
Product Net Height:	0.085 m
Product Net Depth:	0.069 m
Product Net Weight:	0.360 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.082 m
Package Level 1 Height:	0.078 m
Package Level 1 Length:	0.096 m

Package Level 1 Gross Weight:	0.403 kg
Package Level 1 EAN:	8012542784906

Technical

Standards:	EN 61008 UL 1053
Operating Characteristic:	Selective
Type of Residual Current:	A type
Rated Residual Current:	500 mA
Rated Current (I_n):	40 A
Number of Poles:	4
Position of Neutral Terminals:	Right
Power Loss:	at Rated Operating Conditions per Pole 3.2 W
Rated Voltage (U_r):	230/400 V

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q3
--------------	---

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	ITSCE116F200
RoHS Information:	2CSC423001K0201

Classifications

Object Classification Code:	Q
ETIM 4:	EC000003 - Residual current circuit breaker (RCCB)
ETIM 5:	EC000003 - Residual current circuit breaker (RCCB)