



**Electric Automation**  
Automation specialists

Reference: DS203NCLC16APR30  
Code: 2CSR246440R1164

DS203NC L C16 APR30 - RCBO

Buy it at Electric Automation Network



DS203NC is a 3P+N residual current circuit breaker with overcurrent protection (RCBO) in four modules for the protection against short-circuit currents, overload, earth fault currents, indirect contacts, additional protection against direct contacts (30 mA versions).

### Ordering

EAN:	8012542078722
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363010

### Dimensions

Product Net Width:	0.071 m
Product Net Height:	0.085 m
Product Net Depth:	0.069 m
Product Net Weight:	0.480 kg

### Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.076 m
Package Level 1 Height:	0.096 m

Package Level 1 Length:	0.073 m
Package Level 1 Gross Weight:	0.530 kg
Package Level 1 EAN:	8012542078722

## Technical

Standards:	IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1
Type of Residual Current:	A type
Rated Residual Current:	30 mA
Tripping Characteristic:	C
Rated Current ( $I_n$ ):	16 A
Number of Poles:	4
Number of Protected Poles:	3
Rated Short-Circuit Capacity ( $I_{cn}$ ):	(230 / 400 V AC) 4.5 kA
Position of Neutral Terminals:	Right
Power Loss:	10 W

## Environmental

RoHS Status:	Following EU Directive 2011/65/EC
--------------	-----------------------------------

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CSC421010D2701
RoHS Information:	2CSC422009K2702

## Classifications

Object Classification Code:	Q
ETIM 4:	EC000905 - Earth leakage circuit breaker
ETIM 5:	EC000905 - Earth leakage circuit breaker