



Electric Automation
Automation specialists

Reference: JSTD-1B

Code: 2TLA020007R3100

JSTD1-B Safeball 200mm cable

Buy it at [Electric Automation Network](#)

JSTD1-B Safeballs each have 1NO & 1NC independent switches, maximum load of 30VDC - 2A resistive. Ergonomic design with several grip possibilities and low activation force (approx. 2N) and flexible mounting options. Provides highest level of safety for use in two hand control applications when using two Safeballs in conjunction with a JSBR4 safety relay or Pluto Safety PLC. IP67 protection degree, plastic body, 0.2m wires x 4 for direct connection into an enclosure.

Ordering

EAN:	7350024460209
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365011

Dimensions

Product Net Width:	0.072 m
Product Net Height:	0.071 m
Product Net Depth:	0.072 m
Product Net Weight:	0.100 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.190 m
Package Level 1 Height:	0.105 m
Package Level 1 Length:	0.075 m
Package Level 1 Gross Weight:	0.218 kg
Package Level 1 EAN:	7350024460209
Package Level 2 Units:	2 piece
Package Level 2 Width:	0.107 m

Package Level 2 Height:	0.190 m
Package Level 2 Length:	0.178 m
Package Level 2 Gross Weight:	0.252 kg
Package Level 2 EAN:	7350024460193

Safety Information

Performance Level (PL):	Up to e
Safety Category Acc. to ISO 13849-1:	4

Additional Information

Product Main Type:	JSTD1
Product Name:	Two Hand Safety Control Device

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2TLC172001C0202_chapter10
Declaration of Conformity - CE:	2TLC172023D0201

Classifications

E-nummer:	3861302
ETIM 4:	EC002611 - Control switch
ETIM 5:	EC002611 - Control switch
Object Classification Code:	B