



Electric Automation
Automation specialists

Reference: M12-3A
Code: 2TLA020055R0000

M12-3A M12 Y-connector

Buy it at Electric Automation Network



M12 Y connector for series connection of dynamic safety devices such as Eden Sensors, Smile E-Stops, Inca E-Stops, Spot Single Beams, and Tina Dynamic Adapters. 5-pole M12 female connector(2) for connection of the safety device, 5-pole M12 male connector(1) for connecting 24VDC, 0VDC and the dynamic transmit signal to the field devices and 5-pole M12 female connector(3) for either the continuation of the circuit or the return of the dynamic receive signal to the Vital 1/Pluto controller.

Ordering

EAN:	7350024452259
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85444290

Dimensions

Product Net Width:	0.035 m
Product Net Height:	0.04 m
Product Net Depth:	0.02 m
Product Net Weight:	0.028 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	0.10 m
Package Level 1 Height:	0.02 m
Package Level 1 Length:	0.17 m

Package Level 1 Gross Weight:	0.02 kg
-------------------------------	---------

Additional Information

Product Main Type:	Connectors
Product Name:	Connector

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2TLC172001C0202_chapter05
Declaration of Conformity - CE:	NoDecNee

Classifications

E-nummer:	3861400
ETIM 4:	EC002638 - Cable connector
ETIM 5:	EC002638 - Cable connector
Object Classification Code:	X