



Electric Automation
Automation specialists

Reference: 032U6501

Type Code EV210B , Weight 0.184 Kg , Actuator size 13.5 mm ,
Actuator size 0.53 in , Ambient temp. max. 50 °C

Buy it at Electric Automation Network



EV210B covers a wide range of direct-operated 2/2-way solenoid valves for universal use. EV210B is a real robust valve program with high performance and can be used in all kind of tough working conditions.

Type Code	EV210B
Weight	0.184 Kg
Actuator size	13.5 mm
Actuator size	0.53 in
Ambient temp. max.	50 °C
Ambient temp. max.	122 °F
Body mat.	Brass
Connection	NPT 1/8
Conn. Int./Ext.	Internal
Conn. std.	ANSI/ASME B1.20.1
Cv value	0,090 gpm US
Diff. pressure	0 - 20 bar
Diff. pressure	0,0 - 285,7 psi
EAN no.	5702423031559

Function	N C
Kv value	0,080 m3/h
Max. Working Pressure	35,0 bar
Max. Working Pressure	510 psig
Medium temp. range	-10 - 90 °C
Medium temp. range	15 - 195 °F
Number of ways	2/2

Operation	Direct-operated
Orifice size	1,50 mm
Orifice size	1/16 in
Seal mat.	FKM
Type designation	Solenoid valve