	Description	Length m	For use with	Part no. Article no.	<b>Price</b> see price list	Std. pack	Instructions
Power supply at flat ca	able RA-C1						
End-piece for terminating the ribbon	ı cable						
	-		RA-C1-7X4HF	<b>RA-C1-END1</b> 290189		10 off	-
Tools							
	For cutting flat cable		RA-C1-7X4HF	<b>RA-C1-CUT</b> 254690		1 off	-
.0.	for removing casing at the ends of the flat cable		RA-C1-7X4HF	RA-C1-AZ-4 272087		1 off	A standard engineer's pliers is required.
Power supply at round	l cable RA-C2						
Power connection cable for connecting the device	with the round cable junction						
	with power plug and plug for round cable junction, halogen-free, 5 x 15 mm <sup>2</sup>	1.5	RAMO RASP RA-C2-S1-4	RA-C3/C2-1,5HF 290211		1 off	-
Round cable junction							
Connection socket for po							
	for 7 x 2.5/4 mm <sup>2</sup> , 400 V AC and 24 V DC, termination with insulation piercing technology, cable fixing with metal screws, pre-wired socket insert, suitable for cable outer diameters 10 - 13/13 - 16 mm.		RA-C3/C2-1,5HF	<b>RA-C2-S1-4</b> 257830		1 off	Equipment supplied 2 pairs of seals for these cable diameters, 1 lock mechanism
Outgoer plug	connection cable, connection to round cab	ıla hranch					
To dissenting the power	prefabricated plug with 8 x 1.5 mm <sup>2</sup> crimp contacts	<u> </u>	RA-C2-S1-4	<b>RA-C2-PLM</b> 272089		1 off	Tool required: Crimping tool for HAN E contacts from Messrs. Harting Minimum order quantity 10 off
Blanking plug for closing the last round	cable junction in the power line						
	-		RA-C2-S1-4	<b>RA-C2-SBL</b> 265357		10 off	One set with 10 blanking plugs.
Power supply at round	l cable RA-C4						
Round cable junction Connection socket for po	wer cables from 2.5 - 6 mm²						
	T junction via spring-cage terminal, 1.5 to 6 mm² and/or plug connection of 0.5 - 4 mm², Enclosure IP65		RA-C4-PPB/C3- 1M5 RA-C4-X/C3- 1M5	<b>RA-C4-PB65</b> 116905		1 off	Tools required: Stripping tool AM16 from Weidmüller or similar. Enclosure continuous seals must be ordered separately.
Gasket Slotted enclosure bushin	g seal						
	for Ø 11 - 13 mm EPDM round cable, silicon free and halogen free, IP65		RA-C4-PB65	<b>RA-C4-D13</b> 116907		10 off	-
	for Ø 13 - 15 mm EPDM round cable, silicon free and halogen free, IP65	_	RA-C4-PB65	<b>RA-C4-D15</b> 116908		10 off	-
	for Ø 15 - 17 mm EPDM round cable, silicon free and halogen free, IP65		RA-C4-PB65	<b>RA-C4-D17</b> 116909		10 off	-