

Features:
- Rated current 800 – 4000 A
- I_{cc} (400 V AC) up to 100 kA
- Fixed mounted or drawer units
- 3 or 4-pole
- External actuation
- Module height 650 mm



	I_{cc} to (400 V AC)	I_e up to	Installation type	Poles	Section width	**Type Assembly unit**[3] Article no.
	kA	A			mm	1 off each
Air circuit-breaker						
IZMB(N)1-..	65	800 – 1600	Fixed, drawer unit	3	425	**XMI1304** 283955
				4	600	**XMI1406** 283964
			Drawer unit[1]	3	425	**XMI1304-1** 285680
				4	600	**XMI1406-1** 285681
IZMB(N)1-.. IZMB(N,H)2-..	65 100	800 – 1600 800 – 3200	Fixed, drawer unit	3	600	**XMI2306** 283973
				4	800	**XMI2408** 283975
			Drawer unit[1]	3	600	**XMI2306-1** 283974
				4	800	**XMI2408-1** 283976
IZMB(N)1-.. IZMB(N,H)2-.. IZMH3-..	65 100 100	800 – 1600 800 – 3200 4000[2]	Fixed, drawer unit	3	800	**XMI3308** 283977
				4	1200	**XMI3412** 283978

Notes

[1] Only for cable or top busbar connection on top main busbar or cable and busbar connection at bottom of main busbar: The door frontplate has been offset in the circuit-breaker area by approx. 50 mm.
[2] Can only be installed in 800 mm deep sections.
[3] The door seal IZM-XRT and for IP55 protective cover IZM-XDT are always additionally required.