




**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

# Fire protection duct PYROLINE® Sun PV


## Fire protection duct



Type	Dimension h mm	Dimension b mm	Dimension H mm	Dimension B mm	Length mm	Weight kg/100 m	Item No.
<b>BSKP 0406</b>	40	60	80	100	1,000	480.000	<b>7214 70 0</b>

Concrete /m

Fire protection duct for fire-proof routing of photovoltaic cables and inside and outside buildings. Consists of non-conductive, frost-resistant fibre glass lightweight concrete and fulfils the requirements for the contact protection of rescue services in case of fire. Tested and approved to DIN 4102 Part 11, as an I30 duct, may therefore be used in emergency and escape routes. Including lid screws and 3 m of sealing strip.




## End piece



Type	Dimension B mm	Dimension H mm	Pack. pcs	Weight kg/100 pcs.	Item No.
<b>BSKP-E0406</b>	100	80	1	14.000	<b>7214 70 5</b>

Concrete /pc.

End piece for fire protection duct BSKP I30, including bolts and sealing strip.



## Sealing strip



Type	Dimension mm	Length mm	Weight kg/100 pcs.	Item No.
<b>BSKP-D0320</b>	20 x 5	1,000	16.000	<b>7214 71 0</b>

Foam /pc.

Self-adhesive sealing strip for BSKP 0406


## Lid screws




Type	Dimension mm	Pack. pcs	Weight kg/100 pcs.	Item No.
<b>BSK-S0955</b>	4.0 x 55	50	0.340	<b>7215 40 0</b>

**St** Steel **G** Electrogalvanised /100 pc.

Counter-sunk head screw for fire protection duct I90/E30, for lid and doubler fastening.



## Connector for suspended mounting



Type	Weight kg/100 pcs.	Item No.
<b>BSKP-V 0406</b>	22.000	<b>7214 71 5</b>

**St** Steel **FS** Strip-galvanised /pc.

Connection shackle for use of the fire protection duct BSKP 0406, as suspended variant. The set contains 2 connectors and the appropriate quantity of fastening and connection screws.

## Bolt for connector



Type	Dimension	Pack. pcs	Weight kg/100 pcs.	Item No.
<b>BSKP-S5020</b>	5x20	100	0.260	<b>3498 09 8</b>

**St** Steel **GTP** Electrogalvanised, transparently passivated /100 pc.

Bolt with special milled ribs for universal fastening of cable clips, connector elements and separating retainers in fibre glass light-weight concrete of the BSK fire protection ducts.

## Threaded rod



Type	Thread	Dimension d mm	Dimension L mm	Pack. pcs	Weight kg/100 pcs.	Item No.
<b>2078 M10 1M G</b>	M10	10	1,000	25	49.000	<b>3141 20 9</b>

**St** Steel **G** Electrogalvanised /100 pc.

Threaded rod to DIN 976.





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
Bolt with milled ribs, 5x20, Electrogalvanised, transparently passivated, Steel, St	3498098	BSKP-S5020	<a href="#">Buy on EAN</a>
Countersunk head screw for fire protect. duct I90/E30, 4,0x55mm, Electrogalvanised, DIN 50961, Steel, St	7215400	BSK-S0955	<a href="#">Buy on EAN</a>