




Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)



Trunking depth 70 and 90 mm, trunking height 170 mm, asymmetrical



T piece, trunking depth 90 mm

Type	Colour	Surface finish	Dimension a mm	Pack. pcs	Weight kg/100 pcs.	Item No.
GA-AT90170EL	—	Anodised	40	1	136.600	6279 56 3
GA-AT90170RW	Pure white	—	40	1	136.600	6279 56 0


Al Aluminium **EL** Anodised /pc.
T piece for branches of Rapid 80 GA aluminium device installation trunking.



End piece, trunking depth 70 mm

Type	Colour	Surface finish	Pack. pcs	Weight kg/100 pcs.	Item No.
GA-ET70170EL	—	Anodised	1	13.400	6279 47 3
GA-ET70170RW	Pure white	—	1	13.400	6279 47 0


Al Aluminium **EL** Anodised /pc.
End piece for tidy closure of the Rapid 80 GA device installation trunking in aluminium.



End piece, trunking depth 90 mm

Type	Colour	Surface finish	Pack. pcs	Weight kg/100 pcs.	Item No.
GA-E90170EL	—	Anodised	1	16.900	6279 57 3
GA-E90170RW	Pure white	—	1	16.900	6279 57 0


Al Aluminium **EL** Anodised /pc.
End piece for tidy closure of the Rapid 80 GA device installation trunking in aluminium.



Partition, trunking depth 70 mm

Type	Length mm	Suitable for trunking depth	Pack. m	Weight kg/100 m	Item No.
GA-TW70	2000	70	2	51.500	6279 71 1


St Steel /m
Partition to divide the Rapid 80 GA aluminium device installation trunking and ISS service poles for the installation of different voltage levels.



Partition, trunking depth 90 mm

Type	Length mm	Suitable for trunking depth	Pack. m	Weight kg/100 m	Item No.
GA-TW90	2000	90	2	67.300	6279 71 4


St Steel /m
Partition to divide the trunking for different voltage levels for Rapid 80 GA aluminium device installation trunking.



Duct clamp

Type	Pack. pcs	Weight kg/100 pcs.	Item No.
KL80A	20	0.680	6288 64 0

PA Polyamide /pc.
Duct clamp for secure cable holding and fixing the partition in the GK, GS and GA device installation duct and trunking systems.



Protective conductor connection bracket

Type	Pack. pcs	Weight kg/100 pcs.	Item No.
8AWR	10	0.640	6288 70 4

St Steel **G** Electrogalvanised /pc.
Protective conductor connection bracket to include steel and aluminium device installation trunking as well as service poles in the protective measures.
Clamping area : 2 x 1.5 – 4 mm²





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
End piece , 70x170mm, Pure white, 9010, Aluminium, Alu	6279470	GA-ET70170RW	Buy on EAN
End piece , 70x170mm, Anodised, Aluminium, Alu	6279473	GA-ET70170EL	Buy on EAN
T-piece asymmetrical, 90x170mm, Pure white, 9010, Aluminium, Alu	6279560	GA-AT90170RW	Buy on EAN
T-piece asymmetrical, 90x170mm, Anodised, Aluminium, Alu	6279563	GA-AT90170EL	Buy on EAN
End piece , 90x170mm, Pure white, 9010, Aluminium, Alu	6279570	GA-E90170RW	Buy on EAN
End piece , 90x170mm, Anodised, Aluminium, Alu	6279573	GA-E90170EL	Buy on EAN
Partition for GA 70, 53x24x2000, Steel, St	6279711	GA-TW70	Buy on EAN
Partition for GA 90, 73x24x2000, Steel, St	6279714	GA-TW90	Buy on EAN
Trunking clamp for system opening 80, Polyamide, PA	6288640	KL80A	Buy on EAN