At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. HERE

Cross-connector for flat conductors and round cables



Type	Fit mm		Pack. pcs	Weight kg/100 pcs.	Item No.
252 8-10XFL30 FT	8-10 x FL30		25	28.500	**5312 65 5**

St Steel F Hot-dip galvanised /100 pc.

- Fit: Rd 8-10 x FL 30
- Installed with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8





Type	Fit mm		Pack. pcs	Weight kg/100 pcs.	Item No.
252 8-10xFL30V4A	8-10 x FL30		25	28.500	**5312 65 6**

V4A Stainless steel, grade 316 Ti

- Fit: Rd 8-10 x FL 30
- Installed with 4 hexagonal bolts M8 x 25 and 4 hexagonal nuts M8



Cross-connector for flat conductors and round cables



Type	Fit mm		Pack. pcs	Weight kg/100 pcs.	Item No.
250	Rd 8-10/FL30		25	10.260	**5312 90 6**

St Steel FT Hot-dip galvanised /100 pc.

- Fit: Rd 8-10 x Rd 8-10
- Fit: Rd 8-10 x FL 30
- Fit: FL 30 x FL 30
- Installed with 2 hexagonal bolts M8 x 20 (F)



Type	Fit mm		Pack. pcs	Weight kg/100 pcs.	Item No.
250 VA	Rd 8-10/FL30		25	10.260	**5312 92 2**
250 V4A	Rd 8-10/FL30		25	10.260	**5312 92 5**

V2A Stainless steel, grade 304 V4A Stainless steel, grade 316 Ti /100 pc.

- Fit: Rd 8-10 x Rd 8-10
- Fit: Rd 8-10 x FL 30
- Fit: FL 30 x FL 30
- Installed with 2 hexagonal bolts M8 x 20 (F)

Diagonal clamp



Type	Dimension L mm	Fit mm		Pack. pcs	Weight kg/100 pcs.	Item No.
250 A-FT	40	Rd 6-22/max. FL50		25	28.800	**5313 01 5**
250 AS-FT	20	Rd 6-22/max. FL50		25	26.000	**5313 03 1**

St Steel FT Hot-dip galvanised /100 pc.

- For reinforced steels Ø 6-22 mm and flat conductor 50 x 4
- Installed with screws M10 x 40
- AS version with screws M10 x 20
- Simple installation with open slot



Type	Dimension L mm	Fit mm		Pack. pcs	Weight kg/100 pcs.	Item No.
250 A-VA	40	Rd 6-22/max. FL50		25	28.800	**5313 02 3**

V2A Stainless steel, grade 304 /100 pc.

- For reinforced steels Ø 6-22 mm and flat conductor 50 x 4
- Installed with screws M10 x 40
- AS version with screws M10 x 20
- Simple installation with open slot

Diagonal clamp with bolt



Type	Dimension L mm	Fit mm		Pack. pcs	Weight kg/100 pcs.	Item No.
250 A-BO	25	Rd 6-22/max. FL50		25	30.000	**5313 06 6**

St Steel F Hot-dip galvanised /100 pc.

- For reinforced steels Ø 6-22 mm and flat conductor 50 x 4
- Installed with screws M10 x 25
- Simple installation with open slot
- With flange-welded bolts M10 x 40, inc. 2 washers and 2 nuts

Always indicate the item number when ordering.

Automatización Eléctrica
Especialistas en Automatización

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Cross-connectors , 8-10mm, Hot-dip galvanised, DIN 267, Teil 10, Steel, St	5312655	252 8-10XFL30 FT	Buy on EAN
Cross-connectors , Stainless steel, grade 304, VA, 1.4301	5312922	250 VA	Buy on EAN
Cross-connectors , 8-10mm, Stainless steel, grade 316 Ti, VA, 1.4571	5312925	250 V4A	Buy on EAN
Diagonal clamp , Hot-dip galvanised, DIN EN ISO 1461, Steel, St	5313015	250 A-FT	Buy on EAN
Diagonal clamp , Stainless steel, grade 304, VA, 1.4301	5313023	250 A-VA	Buy on EAN
Diagonal clamp , Hot-dip galvanised, DIN EN ISO 1461, Steel, St	5313031	250 AS-FT	Buy on EAN
Diagonal clamp with flange-welded bolt, Hot-dip galvanised, DIN 267, Teil 10, Steel, St	5313066	250 A-BO	Buy on EAN