



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

Interception rod systems




isFang-3B threaded rod

Type	Dimension L mm	Pack. pcs	Weight kg/100 pcs.	Item No.
isFang 3B-G1	270	3	48.000	5408 97 1
isFang 3B-G2	340	3	60.400	5408 97 2
isFang 3B-G3	430	3	76.600	5408 97 3

V2A Stainless steel, grade 304

/pc.

Threaded rod to fasten 1, 2 or 3 FangFix concrete bases with tripod stand. To mount the threaded rods, the edge protection must be drilled.




Concrete block for FangFix-System 16 kg

Type	Nominal size Ø mm	Pack. pcs	Weight kg/100 pcs.	Item No.
F-FIX-S16	365	1	1,700.000	5403 22 7

/100 pc.

- 16 kg stone of Ø 365 mm, high level of stability
- Concrete, frost-resistant
- Stackable




Base for FangFix system 16 kg for mounting the isFang tripod

Type	Nominal size Ø mm	Dimension D mm	Pack. pcs	Weight kg/100 pcs.	Item No.
F-FIX-B16 3B	373	25	10		5403 23 8

PP Polypropylene

- Edge protection with through hole
- For mounting isFang-3B threaded rod and FangFix concrete block F-FIX-S16




Insulated interception rod for inner-routed isCon cable

Type	Dimension D Ø mm	Dimension A mm	Dimension H mm	Dimension B mm	Dimension L mm	Length mm	Materials combination	Pack. pcs	Weight kg/100 pcs.	Item No.
isFang IN 4000	50	1,325	1,500	1,000	4,000	4,000	Alu / GFK	1	535.000	5408 93 4
isFang IN 6000	50	3,325	1,500	1,000	6,000	6,000	Alu / GFK	1	835.000	5408 93 6

GFK Fibre-glass-reinforced plastic

/pc.

- For installation of the OBO isCon® cable in the pipe
- For mounting on the building structure
- Inclusive connection element (type isCon IN connect)
- Inclusive potential connection (type isCon In PAE)




isFang support for wall mounting, 15 mm spacing

Type	Dimension D Ø mm	Dimension L mm	Pack. pcs	Weight kg/100 pcs.	Item No.
isFang TW30	-	30	2	62.000	5408 95 2

V2A Stainless steel, grade 304

/pc.

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.




isFang support for wall mounting, 80 mm spacing

Type	Dimension D Ø mm	Dimension L mm	Pack. pcs	Weight kg/100 pcs.	Item No.
isFang TW80	-	80	2	63.000	5408 95 0

V2A Stainless steel, grade 304

/pc.

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.




isFang support for wall mounting, 200-300 mm spacing

Type	Dimension D Ø mm	Dimension L mm	Pack. pcs	Weight kg/100 pcs.	Item No.
isFang TW200	-	300	2	230.000	5408 95 4

V2A Stainless steel, grade 304

/pc.

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
Adjustable floor feet for FangFix, 16kg,	5403227	F-FIX-S16	Buy on EAN
Basic system for FangFix, 16kg, Polypropylene, PP	5403235	F-FIX-B16	Buy on EAN
Basic system for FangFix, 16kg, Black, Polypropylene, PP	5403238	F-FIX-B16 3B	Buy on EAN
Insulated interception rod for isCon cable, internal, 4000mm, Fibre-glass-reinforced plastic, GFK	5408934	isFang IN 4000	Buy on EAN
Insulated interception rod for isCon cable, internal, 6000mm, Fibre-glass-reinforced plastic, GFK	5408936	isFang IN 6000	Buy on EAN
isFang support for wall mounting, 80mm, Stainless steel, grade 304, VA, 1.4301	5408950	isFang TW80	Buy on EAN
isFang support for wall mounting, 200-300mm, Stainless steel, grade 304, VA, 1.4301	5408954	isFang TW200	Buy on EAN
Threaded rod for 1 FangFix concrete stone, 270mm, Stainless steel, grade 304, VA, 1.4301	5408971	isFang 3B-G1	Buy on EAN
Threaded rod for 2 FangFix concrete stones, 340mm, Stainless steel, grade 304, VA, 1.4301	5408972	isFang 3B-G2	Buy on EAN
Threaded rod for 3 FangFix concrete stones, 430mm, Stainless steel, grade 304, VA, 1.4301	5408973	isFang 3B-G3	Buy on EAN