



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)




isCon® arrester

Type	Colour	Cross-section mm ²	Nominal size Ø mm	Normal ring ca. m	Pack. m	Weight kg/100 m	Item No.
isCon 750 SW	Black	35	23	25	25	205.400	5408 00 2
isCon 750 SW	Black	35	23	100	100	103.400	5408 00 4
isCon 750 SW	Black	35	23	250	250	93.400	5408 00 6

/100 m

Surface discharge-free and high voltage-resistant insulated arrester to maintain the separation distance according to IEC 62305.
Equivalent separation spacing $s \leq 0.75$ m in the air.

Please refer to the mounting instructions for information on routing the OBO isCon® cable.




isCon® arrester in light grey

Type	Colour	Cross-section mm ²	Nominal size Ø mm	Normal ring ca. m	Pack. m	Weight kg/100 m	Item No.
isCon 750 LGR	Light grey	35	26	25	25	224.000	5407 99 5
isCon 750 LGR	Light grey	35	26	100	100	122.000	5407 99 7

/100 m

Surface discharge-free and high voltage-resistant insulated arrester to maintain the separation distance according to IEC 62305.
Equivalent separation spacing $s \leq 0.75$ m in the air.

Please refer to the mounting instructions for information on routing the OBO isCon® cable.




Insulation removal pliers

Type	Clamping range D mm	Pack. pcs	Weight kg/100 pcs.	Item No.
isCon stripper	23-26	1	138.000	5408 00 9

/pc.

Pliers to remove the insulation of the OBO isCon® cable.




Spare blade

Type	Dimension	Pack. pcs	Weight kg/100 pcs.	Item No.
isCon cut	34mm	5	1.200	5408 01 1

/pc.

- Replacement blade for replacing the isCon® stripping pliers




Connection element

Type	Dimension D Ø mm	Fit mm	Pack. pcs	Weight kg/100 pcs.	Item No.
isCon connect	23	10	2	21.500	5408 02 2

/pc.

V2A Stainless steel, grade 304

Screw-on termination of the connection for the isCon® cable.
Including heat-shrinkable sleeve and screw lock.




Potential connection

Type	Fit mm	Pack. pcs	Weight kg/100 pcs.	Item No.
isCon PAE	Ø 17-25mm	2	36.500	5408 03 6

/pc.

V2A Stainless steel, grade 304

Potential control to avoid surface discharges on the isCon® cable. Installation takes place after the first 1.5 metres.





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Insulated arrestor 25 m roll, ø 26mm, Light grey,	5407995	isCon 750 LGR	Buy on EAN
Insulated arrestor 100 m roll, ø 26mm, Light grey,	5407997	isCon 750 LGR	Buy on EAN
Insulated arrestor 25 m roll, ø 23mm, Black,	5408002	isCon 750 SW	Buy on EAN
Insulated arrestor 100 m roll, ø 23mm, Black,	5408004	isCon 750 SW	Buy on EAN
Replacement knife for insulation removal pliers, 34mm,	5408011	isCon cut	Buy on EAN
Connection element for isCon cable, ø 23mm, Stainless steel, grade 304, VA, 1.4301	5408022	isCon connect	Buy on EAN
Potential connection for isCon cable, ø 17-25mm, Stainless steel, grade 304, VA, 1.4301	5408036	isCon PAE	Buy on EAN