



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

OBO isCon® system




M-Quick cable bracket PA

| Type | Colour | Clamping range D mm | Pull-out value N | Pack. pcs | Weight kg/100 pcs. | Item No. |
|-----------------|------------|---------------------|------------------|-----------|--------------------|-----------|
| M-Quick M25 SW | Jet black | 20-25 | 50 | 50 | 0.930 | 2153 78 7 |
| M-Quick M32 LGR | Light grey | 25-32 | 60 | 50 | 1.400 | 2153 73 4 |

PA Polyamide

Multi-quick metric.
Simple fastening.
Secure locking.
Radial arrangement.
Simplified storage.
Universally applicable.

/100 pc.




VA roof cable holder, sloping roof

| Type | Installation height mm | Dimension D Ø mm | Pack. pcs | Weight kg/100 pcs. | Item No. |
|------------------|------------------------|------------------|-----------|--------------------|-----------|
| isCon H280 VA | 55 | 23 | 25 | 16.100 | 5408 04 7 |
| isCon H280 26 VA | 55 | 26 | 25 | 16.900 | 5408 07 4 |

V2A Stainless steel, grade 304

To route the isCon® cable on pitched roofs.

/pc.




PA roof cable holder, sloping roof

| Type | Colour | Dimension 280mm | Dimension D Ø mm | Pack. pcs | Weight kg/100 pcs. | Item No. |
|------------------|------------|-----------------|------------------|-----------|--------------------|-----------|
| isCon H280 PA | Black | 280mm | 23 | 25 | 13.950 | 5408 04 9 |
| isCon H280 26 PA | Light grey | 280mm | 26 | 25 | 14.060 | 5408 07 2 |

PA Polyamide

To route the isCon® cable on pitched roofs.

/pc.




Spacer

| Type | Clamping range D mm | Pack. pcs | Weight kg/100 pcs. | Item No. |
|----------|---------------------|-----------|--------------------|-----------|
| isCon DH | 23-26 | 2 | 41.400 | 5408 04 3 |

GFK Fibre-glass-reinforced plastic

For stand-off installation of the isCon® cable in the area of the connection. Incl. reducing sleeve for mounting on FangFix concrete block 10 Kg.

/pc.




Insulated interception rod for inner-routed isCon cable with side exit

| Type | Dimension D Ø mm | Dimension A mm | Dimension H mm | Dimension B mm | Length mm | Materials combination | Pack. pcs | Weight kg/100 pcs. | Item No. |
|------------------|------------------|----------------|----------------|----------------|-----------|-----------------------|-----------|--------------------|-----------|
| isFang IN-A 4000 | 50 | 1,325 | 1,500 | 1,000 | 4,000 | Alu / GFK | 1 | 535.000 | 5408 93 8 |
| isFang IN-A 6000 | 50 | 3,325 | 1,500 | 1,000 | 6,000 | Alu / GFK | 1 | 835.000 | 5408 94 0 |

GFK Fibre-glass-reinforced plastic

- For installation of the OBO isCon® cable in the pipe
- With side cable outlet, fitting tripod stand type isFang 3B-A
- Inclusive connection element (type isCon IN connect)
- Inclusive potential connection (type isCon IN PAE)

/pc.




isFang interception rod stand with side exit

| Type | Dimension B mm | Dimension D Ø mm | Dimension L mm | Dimension H mm | Pack. pcs | Weight kg/100 pcs. | Item No. |
|-----------------|----------------|------------------|----------------|----------------|-----------|--------------------|-----------|
| isFang 3B-100-A | 1,026 | 50 | 600 | 885 | 1 | 6,100.000 | 5408 93 0 |
| isFang 3B-150-A | 1,500 | 50 | 900 | 1,275 | 1 | 950.000 | 5408 93 2 |

V2A Stainless steel, grade 304

- Screwless installation of freestanding interception rods as well as insulated interception rods with 50 mm diameter
- e.g. for internal OBO isCon® cable
- Roof slope to max. 5 degrees
- Incl. Rd 8-10 crossbar for quick round conductor fastening
- Concrete plinths as well as threaded rods should be ordered separately

/pc.





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

| Product | Code | Reference | Product link |
|---|---------|------------------|----------------------------|
| Multi-Quick clip , 25-32mm, Light grey, 7035, Polyamide, PA | 2153734 | M-Quick M32 LGR | Buy on EAN |
| Spacer for FangFix system, 1000mm, Light grey, Fibre-glass-reinforced plastic, GFK | 5408043 | isCon DH | Buy on EAN |
| Roof conductor holder for tiled roofs, 280mm, Stainless steel, grade 304, VA, 1.4301 | 5408047 | isCon H280 VA | Buy on EAN |
| Roof conductor holder for tiled roofs, 280mm, Black, Polyamide, PA | 5408049 | isCon H280 PA | Buy on EAN |
| Tripod stand + outlet for isCon cable, internal, 1,3x1,4m, Stainless steel, grade 304, VA, 1.4301 | 5408930 | isFang 3B-100-A | Buy on EAN |
| Tripod stand + outlet for isCon cable, internal, 1,7x1,9m, Stainless steel, grade 304, VA, 1.4301 | 5408932 | isFang 3B-150-A | Buy on EAN |
| Insul. interception rod+outlet for isCon cable, internal, 4000mm, Fibre-glass-reinforced plastic, GFK | 5408938 | isFang IN-A 4000 | Buy on EAN |
| Insul. interception rod+outlet for isCon cable, internal, 6000mm, Fibre-glass-reinforced plastic, GFK | 5408940 | isFang IN-A 6000 | Buy on EAN |