



Automatización Eléctrica

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)


Base for FangFix system 16 kg for mounting the isFang tripod



Type	Nominal size Ø	Dimension D	Pack.	Weight	Item No.
	mm	mm	pcs	kg/100 pcs.	
F-FIX-B16 3B	373	25	10		5403 23 8

PP Polypropylene

- Edge protection with through hole
- For mounting isFang-3B threaded rod and FangFix concrete block F-FIX-S16



Potential connection clip for mounting on isFang




Type	Fit	Pack.	Weight	Item No.
	mm	pcs	kg/100 pcs.	
927 2 6-K	3/8-4"	10	5.500	5057 59 9

V2A Stainless steel, grade 304

/100 pc.

Potential connection for isCon® cable for mounting on insulated interception rods of type isFang.



Connection plate for one isCon® cable




Type	Dimension	Pack.	Weight	Item No.
		pcs	kg/100 pcs.	
isCon AP1-16 VA	16x8-10mm	1	27.400	5408 02 6

V2A Stainless steel, grade 304

/pc.

Connection plate to connect an isCon® cable with interception rod Ø 16 mm.



Connection plate for two isCon® cables




Type	Dimension	Pack.	Weight	Item No.
		pcs	kg/100 pcs.	
isCon AP2-16 VA	16x8-10mm	1	39.500	5408 02 8

V2A Stainless steel, grade 304

/pc.

Connection plate to connect two isCon® cables with interception rod Ø 16 mm.



Strip clip for fastening the isCon® cable to insulated interception rods




Type	Dimension	Max. bundle Ø	Minimum breaking load kN	Colour	Pack.	Weight	Item No.
	mm	mm			pcs	kg/100 pcs.	
555 7.6x380 SWUV	7.6 x 380	102	0.55	Black	100	0.606	2332 78 4

PA Polyamide

/100 pc.

For rapid fixing, UV and weather-resistant.



Insulated interception rod for inner-routed isCon cable




Type	Dimension D	Dimension A	Dimension H	Dimension B	Length	Materials combination	Pack.	Weight	Item No.
	Ø mm	mm	mm	mm	mm		pcs	kg/100 pcs.	
isFang IN 4000	50	1,325	1,500	1,000	4,000	Alu / GFK	1	535.000	5408 93 4
isFang IN 6000	50	3,325	1,500	1,000	6,000	Alu / GFK	1	835.000	5408 93 6

GFK Fibre-glass-reinforced plastic

/pc.

- For installation of the OBO isCon® cable in the pipe
- For mounting on the building structure
- Inclusive connection element (type isCon IN connect)
- Inclusive potential connection (type isCon In PAE)



isFang support for wall mounting, 15 mm spacing




Type	Dimension D	Dimension L	Pack.	Weight	Item No.
	Ø mm	mm	pcs	kg/100 pcs.	
isFang TW30	—	30	2	62.000	5408 95 2

V2A Stainless steel, grade 304

/pc.

Fastening clip to fasten the insulated support pipes on the structure to be protected or on the wall.





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
Cable tie , 7,6x380mm, Black, Polyamide, PA	2332784	555 7.6x380 SWUV	Buy on EAN
Strip earthing clip , 3/8-4", Stainless steel, grade 304, VA, 1.4301	5057523	927 2	Buy on EAN
Strip earthing clip , 3/8-4", Stainless steel, grade 304, VA, 1.4301	5057599	927 2 6-K	Buy on EAN
Adjustable floor feet for FangFix, 16kg,	5403227	F-FIX-S16	Buy on EAN
Basic system for FangFix, 16kg, Polypropylene, PP	5403235	F-FIX-B16	Buy on EAN
Basic system for FangFix, 16kg, Black, Polypropylene, PP	5403238	F-FIX-B16 3B	Buy on EAN
Connection plate for one isCon cable, 16x8-10mm, Stainless steel, grade 304, VA, 1.4301	5408026	isCon AP1-16 VA	Buy on EAN
Connection plate for two isCon cables, 16x8-10mm, Stainless steel, grade 304, VA, 1.4301	5408028	isCon AP2-16 VA	Buy on EAN
Insulated interception rod for isCon cable, internal, 4000mm, Fibre-glass-reinforced plastic, GFK	5408934	isFang IN 4000	Buy on EAN
Insulated interception rod for isCon cable, internal, 6000mm, Fibre-glass-reinforced plastic, GFK	5408936	isFang IN 6000	Buy on EAN