




**Automatización Eléctrica**

Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)



**Profile rail, slot 11 mm, V2A, unperforated**



Type	Version	Dimension b x h mm	Material thickness mm	Length mm	Bundle m	Weight kg/100 m	Item No.
<b>2060 2M VA</b>	Unperforated	20 x 8	0.75	2000	20	23.550	<b>1105 12 5</b>

**V2A** Stainless steel, grade 304 Bright /100 m

Profile rail with 11 mm slot width.

Static values:


A = 0,303 cm<sup>2</sup>

ly = 0,0275 cm<sup>4</sup>

lz = 0,1711 cm<sup>4</sup>

Wy = 0,028 cm<sup>3</sup>

Wz = 0,1711 cm<sup>3</sup>



**Profile rail, slot 11 mm, perforated**



Type	Version	Dimension b x h mm	Material thickness mm	Length mm	Bundle m	Weight kg/100 m	Item No.
<b>2061 L 2M FS</b>	Perforated	25 x 10	1	2000	50	36.800	<b>1108 12 3</b>

**St** Steel **FS** Strip-galvanised /100 m

Profile rail with 11 mm slot width.

Static values:



A = 0,439 cm<sup>2</sup>

ly = 0,0643 cm<sup>4</sup>

lz = 0,4357 cm<sup>4</sup>

Wy = 0,1223 cm<sup>3</sup>

Wz = 0,3485 cm<sup>3</sup>



**Profile rail, slot 11 mm, unperforated**



Type	Version	Dimension b x h mm	Material thickness mm	Length mm	Bundle m	Weight kg/100 m	Item No.
<b>2061 2M FS</b>	Unperforated	25 x 10	1	2000	50	36.000	<b>1107 12 7</b>

**St** Steel **FS** Strip-galvanised /100 m

Profile rail with 11 mm slot width.

Static values:



A = 0,524 cm<sup>2</sup>

ly = 0,0772 cm<sup>4</sup>

lz = 0,4408 cm<sup>4</sup>

Wy = 0,1299 cm<sup>3</sup>

Wz = 0,3526 cm<sup>3</sup>



**Profile rail, slot 11 mm**



Type	Version	Dimension b x h mm	Material thickness mm	Length mm	Bundle m	Weight kg/100 m	Item No.
<b>2066 2M F</b>	Unperforated	25 x 12	1.5	2000	20	65.000	<b>1117 02 5</b>
<b>2066 2M FS</b>	Unperforated	25 x 12	1.5	2000	20	58.300	<b>1117 03 3</b>
<b>2066 2M VA</b>	Unperforated	25 x 12	1.5	2000	20	58.300	<b>1117 06 8</b>

**St** Steel **V2A** Stainless steel, grade 304 **FS** Strip-galvanised **F** Hot-dip galvanised /100 m

Profile rail, unperforated, slot width 11 mm.

Static values:


A = cm<sup>2</sup>

ly = 0,1389 cm<sup>4</sup>

lz = 0,5908 cm<sup>4</sup>

Wy = 0,1867 cm<sup>3</sup>

Wz = 0,4726 cm<sup>3</sup>



**Profile rail, slot 12 mm, perforated**



Type	Version	Dimension b x h mm	Material thickness mm	Length mm	Bundle m	Weight kg/100 m	Item No.
<b>2062 L 2M FT</b>	Perforated	27 x 12,5	2	2000	20	89.500	<b>1109 52 9</b>

**St** Steel **FT** Hot-dip galvanised /100 m

Profile rail with 12 mm slot width.

Static values:

A = 0,887 cm<sup>2</sup>

ly = 0,1659 cm<sup>4</sup>

lz = 0,9683 cm<sup>4</sup>

Wy = 0,2534 cm<sup>3</sup>

Wz = 0,7173 cm<sup>3</sup>





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
Profile rails unperforated, slot width 11 mm, 2000x20x8, Stainless steel, grade 304, VA, 1.4301	1105125	2060 2M VA	<a href="#">Buy on EAN</a>
Profile rails unperforated, slot width 11 mm, 2000x25x10, Strip-galvanised, DIN EN 10147, Steel, St	1107127	2061 2M FS	<a href="#">Buy on EAN</a>
Profile rails perforated, slot width 11 mm, 2000x25x10, Strip-galvanised, DIN EN 10147, Steel, St	1108123	2061 L 2M FS	<a href="#">Buy on EAN</a>
Profile rails perforated, slot width 12 mm, 2000x27x12,5, Hot-dip galvanised, DIN EN ISO 1461, Steel, St	1109529	2062 L 2M FT	<a href="#">Buy on EAN</a>