At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. HERE

Conductor marker - UC-WMCO 2,9 (21X3,5) OG CUS - 0829072

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Conductor marker, can be ordered: by sheet, orange, labeled according to customer specifications, Mounting type: slide on, Cable diameter: 2.1-2.9 mm, Lettering field: 21 x 3.5 mm

Why buy this product

- The UC-WMCO ... UniCard labeling range includes thread-on markers for the subsequent labeling of conductors by simply sliding them on using the UC-WMCO ... TOOL
- Labeling service: Phoenix Contact can custom-label all UniCard markers according to your requirements

PRINTED FOR YOU

Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 538763

Technical data

Dimensions

Width (a)	21 mm
Cable diameter	2.1 mm ... 2.9 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C

General

Color	orange
Components	free from silicone and halogen
Flammability rating according to UL 94	V2
Material	PA
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	40
Number of individual labels per row	10
Marking mounting type	slide on

Standards and Regulations

Conductor marker - UC-WMCO 2,9 (21X3,5) OG CUS - 0829072

Technical data

Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94	V2

Classifications

eCl@ss

eCl@ss 4.0	24190219
eCl@ss 4.1	24190219
eCl@ss 5.0	27400401
eCl@ss 5.1	27400401
eCl@ss 6.0	27400401
eCl@ss 7.0	27400401
eCl@ss 8.0	27400401

ETIM

ETIM 3.0	EC001530
ETIM 4.0	EC001530
ETIM 5.0	EC001530

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Phoenix Contact 2016 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
Conductor marker, can be ordered: by sheet, orange, labeled according to customer specifications, Mounting type: slide on, Cable diameter: 2.1-2.9 mm, Lettering field: 21 x 3.5 mm	0829072	UC-WMCO 2,9 (21X3,5) OG CUS	Buy on EAN