



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Conductor marking collar - UCT-WMS 4,7 (12X5,5) CUS - 0829953

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Conductor marking collar, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: slide on, for terminal block width: 5.2 mm, Cable diameter: 2.5-4.7 mm, Lettering field: 12 x 5.5 mm



The figure shows the UCT-WMS 4,7 (12x5,5) version in white

Why buy this product

- The UCT-WMS ... UniCard labeling range includes markers that can be threaded onto conductors
- Labeling service: Phoenix Contact can custom-label all UniCard markers according to your requirements
- The markers support multi-line labeling
- The format automatically ensures printing with a high degree of positioning accuracy
- The sheets provide space for including function texts



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 609944

Technical data

Dimensions

Length (b)	12 mm
Width (a)	5.5 mm
Height	7.1 mm
Cable diameter	2.5 mm ... 4.7 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
---------------------------------	-------------------

General

Note	Labeled according to customer specifications
Color	white
Components	free from silicone and halogen
Flammability rating according to UL 94	V0

Conductor marking collar - UCT-WMS 4,7 (12X5,5) CUS - 0829953

Technical data

General

Material	PC V0
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	45
Number of individual labels per row	9
RoHS compliant	Yes
Printability	Thermal transfer Inkjet printing
Device	5146464 THERMOMARK CARD 5147888 BLUEMARK LED 5147999 BLUEMARK CLED
Ink ribbon	5146613 THERMOMARK CARD-UCT-MAG3 0801371 THERMOMARK-RIBBON 110-TC 5147421 BLUEMARK FLUID-CARTRIDGE 5146662 BLUEMARK CLED-FLUID-CARTR.
Test for substances that would hinder coating with paint or varnish	VW PV 3.10.7:2005-02
Result	Test passed
Test specification weathering-resistance	Following ISO 4892-2:2013-03
Test duration	96 h
Wipe resistance test result	Test passed
Salt spray test specification	DIN EN 60068-2-11:2000-02
Test duration	96 h
Salt spray testing result	Test passed
Alternating condensation climate with SO2 test specification	DIN 50018:2013-05
Climate level	AHT 1.0 S
Cycles	2
Condensation test result	Test passed
Wipe resistance of test specification inscriptions	DIN EN 61010-1 (VDE 0411-1):2011-07
Result	Test passed
Marking mounting type	slide on

Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	24190218
eCl@ss 4.1	24190218
eCl@ss 5.0	27141137
eCl@ss 5.1	27141137

Conductor marking collar - UCT-WMS 4,7 (12X5,5) CUS - 0829953

Classifications

eCl@ss

eCl@ss 6.0	27400401
eCl@ss 7.0	27400401
eCl@ss 8.0	27400401

ETIM

ETIM 4.0	EC001530
ETIM 5.0	EC001530

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Conductor marking collar, can be ordered: by sheet, white, labeled according to customer specifications, Mounting type: slide on, for terminal block width: 5.2 mm, Cable diameter: 2.5-4.7 mm, Lettering field: 12 x 5.5 mm	0829953	UCT-WMS 4,7 (12X5,5) CUS	Buy on EAN