



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

# Snap-in markers - US-EMP (35X15) CUS - 0830353

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Snap-in markers, can be ordered: By card, white, labeled according to customer specifications, Mounting type: snapped into marker carrier, Lettering field: 35 x 15 mm



The figure shows a version of the article



## Key Commercial Data

|              |                     |
|--------------|---------------------|
| Packing unit | 1 STK               |
| GTIN         | <br>4 046356 715874 |

## Technical data

### Dimensions

|            |        |
|------------|--------|
| Length (b) | 35 mm  |
| Width (a)  | 15 mm  |
| Height     | 0.5 mm |

### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -30 °C ... 80 °C  |
| Recommended storage conditions  | 10-25 °C / 35-65 % relative humidity. Storage in a cool and dry place is recommended. |

### General

|  |                             |
|--|-----------------------------|
| Color                                  | white                       |
| Components                             | Silicone-free               |
| Flammability rating according to UL 94 | V0                          |
| Material                               | PVC                         |
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels            | 24                          |
| Number of individual labels per row    | 3                           |
| RoHS compliant                         | Yes                         |
| Printability                           | Thermal transfer            |

# Snap-in markers - US-EMP (35X15) CUS - 0830353

## Technical data

### General

|   |                                  |
|---|----------------------------------|
| Device  | 5146464 THERMOMARK CARD          |
|   | 5146451 THERMOMARK CARD-US-MAG1  |
| Ink ribbon  | 0801371 THERMOMARK-RIBBON 110-TC |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02             |
| Result  | Test passed                      |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03     |
| Test duration   | 96 h                             |
| Wipe resistance test result   | Test passed                      |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02        |
| Test duration   | 96 h                             |
| Salt spray testing result   | Test passed                      |
| Alternating condensation climate with SO2 test specification        | Following DIN 50018:2013-05      |
| Climate level   | AHT 1.0 S                        |
| Cycles  | 2                                |
| Condensation test result  | Test passed                      |
| Wipe resistance of test specification inscriptions                  | IEC 61010-1:2010-06              |
| Result  | Test passed                      |
| Foil strength   | 500 µm                           |
| Marking mounting type   | snapped into marker carrier      |

### Standards and Regulations

|  |                             |
|--|-----------------------------|
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94 | V0                          |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27141137 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC000761 |

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 6.01 | 30211811 |
|-------------|----------|

## Snap-in markers - US-EMP (35X15) CUS - 0830353

### Classifications

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

---

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product  | Code    | Reference             | Product link               |
|--|---------|-----------------------|----------------------------|
| Snap-in markers, can be ordered: By card, white, labeled according to customer specifications, Mounting type: snapped into marker carrier, Lettering field: 35 x 15 mm | 0830353 | US-EMP<br>(35X15) CUS | <a href="#">Buy on EAN</a> |