



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

## Cable marker - WMTB HF (40X12)R CUS - 0830413

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable marker, can be ordered: By line, white, labeled according to customer specifications, Mounting type: Assembly with cable binders, Cable diameter:  $\geq 6$  mm, Lettering field: 40 x 12 mm

### Why buy this product

- The marker has two fastening eyes so that it can be attached to the conductor by means of PKB ... cable binders



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 716079

### Technical data

#### Dimensions

Length (b)	40 mm
Width (a)	10 mm

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 80 °C
---------------------------------	------------------

#### General

Color	white
Components	Halogen-free
Flammability rating according to UL 94	V0
Material	PUR
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	1000
Number of individual labels per row	1
Printability	Thermal transfer
Device	5146477 THERMOMARK ROLL
	5146723 THERMOMARK ROLL X1
	5146257 THERMOMARK S1.1

# Cable marker - WMTB HF (40X12)R CUS - 0830413

## Technical data

### General

	5146231 THERMOMARK X1.2
Ink ribbon	5148007 THERMOMARK-RIBBON 110-WMTB HF
Test specification weathering-resistance	VW PV 3.10.7:2005-02
Wipe resistance test result	Test passed
Salt spray test specification	DIN EN 60068-2-11:2000-02
Test duration	96 h
Salt spray testing result	Test passed
Alternating condensation climate with SO2 test specification	DIN 50018:2013-05
Climate level	AHT 1.0 S
Cycles	2
Condensation test result	Test passed
Wipe resistance of test specification inscriptions	IEC 61010-1:2010-06
Result	Test passed
Marking mounting type	Assembly with cable binders

### Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94	V0

## Classifications

### eCl@ss

eCl@ss 4.0	24190219
eCl@ss 4.1	24190219
eCl@ss 5.0	27149103
eCl@ss 5.1	27400401
eCl@ss 6.0	27149103
eCl@ss 7.0	27400401
eCl@ss 8.0	27400401

### ETIM

ETIM 3.0	EC000761
ETIM 4.0	EC001530
ETIM 5.0	EC001530

### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

<b>Product</b>	<b>Code</b>	<b>Reference</b>	<b>Product link</b>
Cable marker, can be ordered: By line, white, labeled according to customer specifications, Mounting type: Assembly with cable binders, Cable diameter: $\geq 6$ mm, Lettering field: 40 x 12 mm	0830413	WMTB HF (40X12)R CUS	<a href="#">Buy on EAN</a>