



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

## Electrical crimping tool - CF 3000-2,5 - 1205477

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Automatic stripping and crimping device, for insulated taped ferrules 0.25 - 2.5 mm<sup>2</sup> according to DIN 46228-4: 1990-09

### Why buy this product

- Thanks to its compact and lightweight design, it can also be used as a portable solution for transport between different work locations
- The automatic device can be adapted to various cross sections in under a minute
- Up to 1200 conductors can be processed an hour
- The compact stripping and crimping machine can be used to process taped ferrules with insulating collars according to DIN 46228-4
- Color coding according to ferrule standard DIN 46228-4 makes the assignment of modification components really clear
- The conductor is stripped in a single step and crimped with a ferrule to a high standard of quality
- Particularly suitable for pre-assembling conductors



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 116910

### Technical data

#### Dimensions

Length (b)	320 mm
Width (a)	165 mm
Height	300 mm

#### General

Compression	trapezoidal
Type of contact	Ferrules
Min. AWG, flexible, multi-strand	14
AWG max., flexible, multi-strand	24
Power consumption	80 VA

# Electrical crimping tool - CF 3000-2,5 - 1205477

## Technical data

### General

Test standard	DIN 46228-4: 1990-09
Min. cross section	0.25 mm <sup>2</sup>
Max. cross section	2.5 mm <sup>2</sup>
AWG min	24
AWG max	14

### Standards and Regulations

Test standard	DIN 46228-4: 1990-09
---------------	----------------------

## Classifications

### eCl@ss

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	17130101
eCl@ss 7.0	17130101
eCl@ss 8.0	17130101
eCl@ss 9.0	17130101

### ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186
ETIM 5.0	EC002778

### UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

## Approvals

### Approvals

#### Approvals

#### EAC

## Electrical crimping tool - CF 3000-2,5 - 1205477

### Approvals

Ex Approvals

---

Approvals submitted

---

### Approval details

EAC
-----

---

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Automatic stripping and crimping device, for insulated taped ferrules 0.25 - 2.5 mm <sup>2</sup> according to DIN 46228-4: 1990-09	1205477	CF 3000-2,5	<a href="#">Buy on EAN</a>