



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

FO patch cable - FOC-ST:A-LC:A-GZ02/2 - 1400702

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled FO cable, zip cord cable, multi-mode fiberglass 50/125 µm, OM3, plug: LC/B-FOC (ST), degree of protection: IP20, for installation in cable ducts or control cabinets, length: 2 m

Why buy this product

- Multi-mode patch cable for indoor installation
- Ideal for use in distributor systems and for connecting termination devices
- UL approval type OFNR (riser) for USA and Canada
- 2.8 mm single elements made from halogen-free and flame-retardant material
- Low-bend fiber

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 735049

Technical data

Mechanical characteristics

Number of positions	2
Fiber	50/125 µm OM3
Type of cable	Zip cord
Length of cable	2 m
Color	blue

Ambient conditions

Ambient temperature (operation)	-10 °C ... 60 °C
Ambient temperature (assembly)	-5 °C ... 50 °C
Ambient temperature (storage/transport)	-10 °C ... 60 °C

Material data

Flammability rating according to UL 94	V0
External sheath, color	aqua
Ferrule material	Zirconia ceramics

Electrical characteristics

FO patch cable - FOC-ST:A-LC:A-GZ02/2 - 1400702

Technical data

Electrical characteristics

Transmission speed	OM3
--------------------	-----

Standards and Regulations

Halogen-free	complying with IEC 60754-1/2
Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27061803
eCl@ss 6.0	27260705
eCl@ss 7.0	27440309
eCl@ss 8.0	27061003

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC000034
ETIM 5.0	EC001263

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Assembled FO cable, zip cord cable, multi-mode fiberglass 50/125 μm , OM3, plug: LC/B-FOC (ST), degree of protection: IP20, for installation in cable ducts or control cabinets, length: 2 m	1400702	FOC-ST:A-LC:A-GZ02/2	Buy on EAN