



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

## Sensor/Actuator cable - SAC-4P-3,0-600/M12FR-3L HD - 1403965

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/Actuator cable, 4-position, PP-EPDM halogen-free, gray RAL 7035, free cable end, on Socket angled M12, A-coded, with 3 LEDs, Cable length: 3 m, Hygienic design, With high-grade steel knurl

### Why buy this product

- Easy and safe: 100% electrically tested plug-in components
- Easy to clean, thanks to the special hygienic design
- Corrosion protection for all exposed metal parts, thanks to the use of stainless steel type 1.4404
- Contamination can be detected quickly – thanks to the light color
- Convenient: increased machine availability thanks to quick and easy diagnostics

### Key Commercial Data

|              |                     |
|--------------|---------------------|
| Packing unit | 1 STK               |
| GTIN         | <br>4 046356 677219 |

### Technical data

#### Dimensions

|                 |     |
|-----------------|-----|
| Length of cable | 3 m |
|-----------------|-----|

#### Ambient conditions

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Ambient temperature (operation) | -40 °C ... 105 °C (Plug / socket) |
| Degree of protection            | IP65                              |
|                                 | IP67                              |
|                                 | IP68                              |
|                                 | IP69K                             |

#### General

|                       |  |
|-----------------------|--|
| Rated current at 40°C | 4 A                                      |
| Rated voltage         | 24 V                                     |
| Number of positions   | 4  |
| Insulation resistance | ≥ 100 MΩ                                 |
| Coding                | A - standard                             |
| Standards/regulations | M12 connector IEC 61076-2-101            |
|                       | Material conformance FDA 21 CFR 177.2600 |

# Sensor/Actuator cable - SAC-4P-3,0-600/M12FR-3L HD - 1403965

## Technical data

### General

|                              |                        |
|------------------------------|------------------------|
| Status display               | 3 LEDs                 |
| Protective circuit/component | Unwired                |
| Overvoltage category         | II                     |
| Degree of pollution          | 3                      |
| Insertion/withdrawal cycles  | ≥ 100                  |
| Torque                       | 0.4 Nm (M12 connector) |

### Material

|                          |                  |
|--------------------------|------------------|
| Contact material         | CuSn             |
| Contact surface material | Ni/Au            |
| Contact carrier material | PP               |
| Material of grip body    | PP               |
| Material, knurls         | High-grade steel |
| Sealing material         | FKM              |

### Standards and Regulations

|                       |                      |
|-----------------------|----------------------|
| Standard designation  | M12 connector        |
| Standards/regulations | IEC 61076-2-101      |
| Standard designation  | Material conformance |
| Standards/regulations | FDA 21 CFR 177.2600  |

### Cable

|   |                                       |
|---|---------------------------------------|
| Cable type                                      | Halogen-free PP gray                  |
| Cable type (abbreviation)                       | 600                                   |
| Cable abbreviation                              | Li9Y9Y                                |
| Conductor cross section                         | 4x 0.34 mm <sup>2</sup> (Signal line) |
| AWG signal line                                 | 22                                    |
| Conductor structure signal line                 | 42x 0.10 mm                           |
| Core diameter including insulation              | 1.27 mm ±0.02 mm (Signal line)        |
| Thickness, insulation                           | ≥ 0.21 mm (Core insulation)           |
| Wire colors                                     | brown, white, blue, black             |
| Overall twist                                   | 4 wires, twisted                      |
| Length of twist, overall twist                  | 48 mm                                 |
| External sheath, color                          | gray RAL 7035                         |
| Outer sheath thickness                          | approx. 0.8 mm                        |
| External cable diameter D                       | 4.7 mm ±0.15 mm                       |
| Minimum bending radius, fixed installation      | 5 x D                                 |
| Minimum bending radius, flexible installation   | 10 x D                                |
| Number of bending cycles                        | 4000000                               |
| Minimum bending radius, drag chain applications | 10 x D                                |
| Traversing path                                 | 10 m                                  |
| Traversing rate                                 | 3 m/s                                 |

# Sensor/Actuator cable - SAC-4P-3,0-600/M12FR-3L HD - 1403965

## Technical data

### Cable

|                                 |   |
|---------------------------------|---|
| Acceleration                    | 10 m/s <sup>2</sup>   |
| Torsion force                   | ± 270 °/m (4,000,000 torsion cycles, max. 25 torsion cycles/min)                  |
| Cable weight                    | 30 kg/km  |
| Outer sheath, material          | PP-EPDM   |
| Material conductor insulation   | PP  |
| Conductor material              | Bare Cu litz wires  |
| Conductor resistance            | 58 Ω/km (at 20 °C)  |
| Nominal voltage, cable          | ≤ 300 V AC  |
| Test voltage, cable             | ≥ 3000 V AC (Spark test)  |
| Special properties              | FDA compliant according to FDA 21 CFR 177.2600                                    |
|                                 | highly flexible   |
|                                 | Flexible cable conduit capable  |
| Halogen-free                    | in accordance with DIN VDE 0472 part 815  |
| Other resistance                | Resistant to cold bending and cold impacts According to DIN EN 60811-1-4 (-40 °C) |
| Ambient temperature (operation) | -40 °C ... 105 °C (cable, fixed installation)                                     |
|                                 | -25 °C ... 105 °C (cable, flexible installation)                                  |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |
| eCl@ss 8.0 | 27279218 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |


### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |

## Drawings


# Sensor/Actuator cable - SAC-4P-3,0-600/M12FR-3L HD - 1403965

Schematic diagram




Pin assignment M12 socket, 4-pos., A-coded, view female side

Cable cross section




Halogen-free PP gray [600]

Dimensional drawing



Socket M12 x 1, angled, with LED

Circuit diagram



Contact assignment of the M12 plug and the M12 socket

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product   | Code    | Reference                      | Product link               |
|---|---------|--------------------------------|----------------------------|
| Sensor/Actuator cable, 4-position, PP-EPDM halogen-free, gray RAL 7035, free cable end, on Socket angled M12, A-coded, with 3 LEDs, Cable length: 3 m, Hygienic design, With high-grade steel knurl | 1403965 | SAC-4P-3,0-600/<br>M12FR-3L HD | <a href="#">Buy on EAN</a> |