



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Network cable - VS-OE-OE-94A-100,0 - 1416305

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Network cable, Ethernet CAT5 (1 Gbps), 8-position, PUR, water blue RAL 5021, shielded, free cable end, on free cable end, Cable length: 100 m

Ethernet

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 473545

Technical data

Dimensions

Length of cable	100 m
-----------------	-------

General data

Number of positions	8
Signal type/category	Ethernet CAT5 (IEC 11801), 1 Gbps

Cable

Cable type	Ethernet
Cable type (abbreviation)	94A
UL AWM style	20549 (80°C/300 V)
Cable structure	4x2xAWG24/1; SF/UTP
Conductor cross section	4x 2x 0.25 mm ²
AWG signal line	24
Conductor structure signal line	1x 0.50 mm
Core diameter including insulation	1.1 mm ±0.05 mm
Wire colors	white/blue-blue, white/orange-orange, white/green-green, white/brown-brown
Twisted pairs	2 cores to the pair
Overall twist	4 pairs for core
Shielding	Aluminum-lined polyester foil, tinned copper braided shield
Optical shield covering	85 %
External sheath, color	water blue RAL 5021

Network cable - VS-OE-OE-94A-100,0 - 1416305

Technical data

Cable

Outer sheath thickness	0.4 mm
External cable diameter D	6.4 mm ±0.2 mm
Smallest bending radius, fixed installation	30 mm
Smallest bending radius, movable installation	60 mm (for installation)
Tensile strength short-term/long-term	80 N
Outer sheath, material	PUR
Material conductor insulation	PE
Conductor material	Bare Cu wire
Insulation resistance	≥ 5 GΩ*km
Conductor resistance	< 93.8 Ω/km
Cable capacity	< 56 nF/km
	< 1600 pF/km (Pair-Ground)
Signal speed	0.6 c
Signal runtime	5.7 ns/m
Nominal voltage, cable	72 V DC
	300 V AC (in acc. with UL)
Test voltage Core/Core	2500 V DC
Flame resistance	According to FT-2
Halogen-free	According to IEC 60754-2
Resistance to oil	According to IEC 60811-2-1
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (installation)	0 °C ... 50 °C

Classifications

eCl@ss

eCl@ss 4.0	27060307
eCl@ss 4.1	27060307
eCl@ss 5.0	27060307
eCl@ss 5.1	27060307
eCl@ss 6.0	27060307
eCl@ss 7.0	27060307
eCl@ss 8.0	27061801

ETIM

ETIM 3.0	EC000830
ETIM 4.0	EC000830
ETIM 5.0	EC000830

UNSPSC

UNSPSC 6.01	26121616
-------------	----------

Network cable - VS-OE-OE-94A-100,0 - 1416305


Classifications

UNSPSC

UNSPSC 7.0901	26121616
UNSPSC 11	26121604
UNSPSC 12.01	31261501
UNSPSC 13.2	26121616

Drawings

Cable cross section



Ethernet [94A]

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Network cable, Ethernet CAT5 (1 Gbps), 8-position, PUR, water blue RAL 5021, shielded, free cable end, on free cable end, Cable length: 100 m	1416305	VS-OE-OE-94A-100,0	Buy on EAN