



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Housing - PV-MI-CABLE SPLICE 3P - 1812403

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Housing to protect splice connection of solar panel wires. Allows splice of 3 conductors (1.5 to 25 mm²/16 to 4 AWG maximum) to be inside housing with an IP67 rating.

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 738682

Technical data

General data

Number of positions	3
Color	black
Insertion/withdrawal cycles	10 (with same cable diameter)

Connection data

Rated current	30 A
Conductor cross section flexible min.	1.5 mm ²
Conductor cross section flexible max.	25 mm ²
Conductor cross section solid min.	1.5 mm ²
Conductor cross section solid max.	25 mm ²
Conductor cross section AWG max.	4
Conductor cross section AWG min.	16
Stripping length	12 mm
Torque	2.5 Nm ... 3 Nm (Conductors)
Wrench size, union nut	22.00 mm

Classifications

eCl@ss

eCl@ss 4.0	27060306
eCl@ss 4.1	27060306
eCl@ss 5.0	27061801
eCl@ss 5.1	27061801

Housing - PV-MI-CABLE SPLICE 3P - 1812403

Classifications

eCl@ss

eCl@ss 6.0	27061801
eCl@ss 7.0	27061801
eCl@ss 8.0	27440401
eCl@ss 9.0	27440401

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002643

UNSPSC

UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Housing to protect splice connection of solar panel wires. Allows splice of 3 conductors (1.5 to 25 mm ² /16 to 4 AWG maximum) to be inside housing with an IP67 rating.	1812403	PV-MI-CABLE SPLICE 3P	Buy on EAN