



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. HERE



# Sleeve housing - VC-K-T1-Z-M20 - 1852935

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Sleeve housing, plastic, with metric cable outlet, locking screws with cylinder head, type: VC1, cable screw

#### Why buy this product

- Seals with two cable entries are available
- Angled cable outlet so the cable can be routed as desired, from the side and straight

### **Key Commercial Data**

Packing unit	5 STK
GTIN	4 017918 970819

### Technical data

#### **Dimensions**

Height	65 mm
Ambient conditions	

#### Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C 80 °C

#### General

Note	When using fiber optics, the bending radii of the cable manufacturers must be observed.		
Туре	VC1		
Degree of protection	IP65		
Flammability rating according to UL 94	V0		
Locking type	Screw locking, cylinder head		
Fixing screws	M4		
Tightening torque, mounting screw	1.5 Nm ±0.3 Nm		
Type of the screw connection	M20		
Pg screw connection	none		
Cable exit	Angled		
Housing material	Polyamide		
Seal material	EPDM		



# Sleeve housing - VC-K-T1-Z-M20 - 1852935

# Technical data

### General

Ambient temperature (operation)	-40 °C 80 °C
Standards and Regulations	

Flammability rating according to UL 94	V0

# Classifications

# eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27371205
eCl@ss 5.1	27371205
eCl@ss 6.0	27371205
eCl@ss 7.0	27371205
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

#### **ETIM**

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

# Approvals

### Approvals

Approvals

EAC

Ex Approvals

Approvals submitted



# Sleeve housing - VC-K-T1-Z-M20 - 1852935


# Approvals

#### Approval details


EAC

# Drawings


### Dimensional drawing



#### Dimensional drawing



#### Dimensional drawing



Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, <u>click on the green button</u>.

Product	Code	Reference	Product link
Sleeve housing, plastic, with metric cable outlet, locking screws with cylinder head, type: VC1, cable screw connection: M20	1852935	VC-K-T1-Z- M20	Buy on EAN