



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Input module - UM-2KS40/16AI/SI/RS/SO225 - 2319841

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



16-channel analog input module with screw connection and redundant voltage supply. Suitable for Yokogawa SAI 143 card.



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 440325

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	250 mm
Height	126 mm
Depth	96 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 55 °C
---------------------------------	------------------

General

Note	Voltage monitoring on the module does not work in combination with upstream HESILED fuse terminal blocks with integrated LED display.
Max. perm. operating voltage	30 V DC
Max. perm. current (per branch)	1 A
Max. permissible current (all branches)	10 A
Number of positions	50
Mounting position	any
Designation	Air clearances and creepage distances
Standards/regulations	DIN EN 50178

Input module - UM-2KS40/16AI/SI/RS/SO225 - 2319841

Technical data

General

Rated insulation voltage	50 V
Rated surge voltage	0.8 kV (basic insulation)
Degree of pollution	2
Overvoltage category	III

Connection data for connection 1

Connection name	Field level
Connection method	Screw connection
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12
Number of positions	48

Connection data for connection 2

Connection name	Controller level
Connection method	Yokogawa KS-compatible
Torque	0.5 Nm
Number of connections	2
Number of positions	40

Connection data for connection 3

Connection name	Supply
Connection method	Screw connection
Number of connections	1
Number of positions	6

Supported controller

Controller	YOKOGAWA ProSafe-RS
- suitable I/O card	SAI143

Standards and Regulations

Designation	Air clearances and creepage distances
Standards/regulations	DIN EN 50178
Degree of pollution	2
Overvoltage category	III

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313

Input module - UM-2KS40/16AI/SI/RS/SO225 - 2319841

Classifications

eCl@ss

eCl@ss 6.0	27242608
eCl@ss 7.0	27242608
eCl@ss 8.0	27141152

ETIM

ETIM 3.0	EC001604
ETIM 4.0	EC001437
ETIM 5.0	EC002780

UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121515
UNSPSC 11	39121515
UNSPSC 12.01	26121620
UNSPSC 13.2	39121515

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
16-channel analog input module with screw connection and redundant voltage supply. Suitable for Yokogawa SAI 143 card.	2319841	UM-2KS40/16AI/SI/RS/SO225	Buy on EAN