



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

Tablet PC - ITC 8113 SW7U - 2402958

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Tablet PC with 33.8 cm/13.3" TFT-Display (Capacitive multi-touch screen), 1920 x 1080 (FHD), Intel® Celeron® 2980U 1,60 Ghz, 2x USB 3.0, 1x USB 3.0 inset, WLAN 802.11 a/g/n, UMTS/LTE, 1 x Ethernet (10/100/1000 Mbps), RJ45, MS Windows® 7 Ultimate (64-Bit).



Similar figure

Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 176383

Technical data

Dimensions

External dimension, width	356 mm
External dimension, height	262 mm
External dimension, depth	42 mm
Note regarding external dimension	73 mm with folded-out supporting feet

Display

Display	33.8 cm/13.3" TFT
Resolution	1920 x 1080 (FHD)
Backlighting	LED
Display backlight MTBF	> 50000 h
Touch screen	Capacitive multi-touch screen
Operating Buttons on the Front	6 additional keys (on/off button, software keyboard, switch task Alt + ESC, right mouse button, user-specific function, SHIFT key (brightness and volume))

Computer data

Processor	Intel® Celeron® 2980U 1,60 Ghz
Processor fan	with fan
Operating systems	MS Windows® 7 Ultimate (64-Bit)
RAM	4 GB DDR3
Mass storage	2,5" SSD, 120 GB (SATA)
Network	1 x Ethernet (10/100/1000 Mbps), RJ45
Interfaces	2x USB 3.0

Tablet PC - ITC 8113 SW7U - 2402958

Technical data

Computer data

	1x USB 3.0 inset
	WLAN 802.11 a/g/n
	UMTS/LTE
Audio	Integrated stereo loudspeakers
	Microphone
Camera	5 megapixels with mechanical autofocus
Graphics card	Intel® HD Graphics

General

Mounting type	Mobile application
Weight	1800 g

Ambient conditions

Degree of protection	IP65 (on the front), IP53 (on the back)
Ambient temperature (operation)	0 °C ... 40 °C
Permissible humidity (operation)	10 % ... 85 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 85 % (non-condensing)

Device supply

Power supply unit	20 V/3.5 A external
Battery type	Lithium-ion smart battery
Number of battery slots	2

Classifications

eCl@ss

eCl@ss 4.0	27360102
eCl@ss 4.1	27360102
eCl@ss 5.0	27360102
eCl@ss 5.1	27242301
eCl@ss 6.0	27242301
eCl@ss 7.0	27242301
eCl@ss 8.0	27242301
eCl@ss 9.0	19200103

ETIM

ETIM 3.0	EC001414
ETIM 4.0	EC001413
ETIM 5.0	EC001414

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404

Tablet PC - ITC 8113 SW7U - 2402958

Classifications

UNSPSC

UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Tablet PC with 33.8 cm/13.3" TFT-Display (Capacitive multi-touch screen), 1920 x 1080 (FHD), Intel® Celeron® 2980U 1,60 Ghz, 2x USB 3.0, 1x USB 3.0 inset, WLAN 802.11 a/g/n, UMTS/LTE, 1 x Ethernet (10/100/1000 Mbps), RJ45, MS Windows® 7 Ultimate (64-Bit).	2402958	ITC 8113 SW7U	Buy on EAN