



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

Touch panel - HTP105XIT - 2700293

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 26.4 cm/10.4" TFT-Display (Resistive industrial touch screen), 800 x 600 Pixel (SVGA), 65536 colors, Xscale® PXA320, 806 MHz, 1 x USB, 1 x Ethernet (10/100 Mbps), RJ45, Windows CE 5.0 and User software: NetCap / Portico. (Bus system: without)

The figure shows a similar product

Why buy this product

- Hand-held operator panel with software for on-site visualization or multi-user operation
- All-round protection (IP65)
- Suitable for drops from up to 1 m
- Energy efficient due to LED backlighting
- 3-stage enable switch, with key switch as an option, and/or stop button

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 532747

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---------------------------------------------------------------------------

Dimensions

External dimension, width	311 mm
External dimension, height	281 mm
External dimension, depth	135 mm

Display

Display	26.4 cm/10.4" TFT
Resolution	800 x 600 Pixel (SVGA)
Backlighting	CCFL
Display backlight MTBF	50000 h
Touch screen	Resistive industrial touch screen
Operating Buttons on the Front	3-stage enable switch (2-channel), integrated in the handle
Colors	65536 colors

Touch panel - HTP105XIT - 2700293

Technical data

Computer data

Processor	Xscale® PXA320, 806 MHz
Operating systems	MS Windows® CE 5.0
User software	NetCap
	Portico
RAM	128 MB SDRAM
Mass storage	1 GB Flash
Network	1 x Ethernet (10/100 Mbps), RJ45
Interfaces	1 x USB
Bus system	without
Slots	without slots

Ambient conditions

Degree of protection	IP65
----------------------	------

Classifications

eCl@ss

eCl@ss 5.1	27242302
eCl@ss 6.0	27242302
eCl@ss 8.0	27242302

ETIM

ETIM 3.0	EC001412
ETIM 4.0	EC001412
ETIM 5.0	EC001412

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

Product	Code	Reference	Product link
Mobile touch panel with 26.4 cm (10.4") graphics-capable TFT display, 65,535 colors, 800 x 600 pixels, 1 x Ethernet incl. accessories	2700293	HTP105XIT	Buy on EAN