



At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. HERE



# Termination resistor - FL LCX 50-OHM - 2884978

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



A termination resistor must be screwed on at the end of the leaky wave conductor which does not contain any wireless part. It guarantees an antenna cable termination with the correct impedance and is important for every wireless installation.

## **Key Commercial Data**

Packing unit	1 STK		
GTIN	4 046356 173162		

## Technical data

#### General

Frequency range	2.4 GHz 6 GHz	
Impedance	50 Ω	
Connection method	N (male)	

## Classifications

## eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	19070403
eCl@ss 5.1	19070403
eCl@ss 6.0	19070490
eCl@ss 7.0	19070490
eCl@ss 8.0	19070403

#### **ETIM**

ETIM 3.0	EC000448
ETIM 4.0	EC000448
ETIM 5.0	EC000448

## **UNSPSC**

	1
UNSPSC 6.01	20142601



# Termination resistor - FL LCX 50-OHM - 2884978

## Classifications

## **UNSPSC**

UNSPSC 7.0901	20142601
UNSPSC 11	20142601
UNSPSC 12.01	20142601
UNSPSC 13.2	20142601

Phoenix Contact 2016 @ - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com





Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, click on the green button.

Product	Code	Reference	Product link
A termination resistor must be screwed on at the end of the leaky wave conductor which does not contain any wireless part. It guarantees an antenna cable termination with the correct impedance and is important for every wireless installation.	2884978	FL LCX 50- OHM	Buy on EAN