



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Industrial Ethernet Switch - FL SWITCH SFN 5TX-24VAC - 2891021

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ethernet switch, 5 TP RJ45 ports, automatic detection of data transmission speed of 10 or 100 Mbps (RJ45), autocrossing function

Why buy this product

- Auto negotiation and autocrossing detection simplifies installation and setup
- Local diagnostic indicators with LEDs
- The switch also offers cable locking and port blocking
- QoS-prioritized (Quality of Service) messages
- RJ45 ports support a transmission speed of 10/100 Mbps; fiber optic ports support 100 Mbps
- DC and AC power supplies

Ethernet

Key Commercial Data

| | |
|--------------|---------------------|
| Packing unit | 1 STK |
| GTIN | 4 046356 457156 |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|--------|--------|
| Width | 30 mm |
| Height | 120 mm |
| Depth | 70 mm |

Ambient conditions

| | |
|--|--|
| Degree of protection | IP20 |
| Ambient temperature (operation) | 0 °C ... 60 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 5 % ... 95 % (non-condensing) |
| Air pressure (operation) | 86 kPa ... 108 kPa (up to 1500 m above mean sea level) |

Industrial Ethernet Switch - FL SWITCH SFN 5TX-24VAC - 2891021

Technical data

Ambient conditions

| | |
|----------------------------------|--|
| Air pressure (storage/transport) | 66 kPa ... 108 kPa (up to 3500 m above mean sea level) |
|----------------------------------|--|

Interfaces

| | |
|---------------------------|-----------------------------------|
| Interface 1 | Ethernet (RJ45) |
| No. of ports | 5 (RJ45 ports) |
| Connection method | RJ45 |
| Note on connection method | Auto negotiation and autocrossing |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission speed | 10/100 MBit/s |

Function

| | |
|----------------------------------|---|
| Basic functions | Unmanaged switch / auto negotiation, complies with IEEE 802.3, store and forward switching mode |
| Status and diagnostic indicators | LEDs: U _S , link and activity per port |

Network expansion parameters

| | |
|---|--|
| Cascading depth | Network, linear, and star structure: any |
| Maximum conductor length (twisted pair) | 100 m |

Supply voltage

| | |
|-----------------------------|--|
| Supply voltage | 24 V AC/DC |
| Residual ripple | 3.6 V _{PP} (within the permitted voltage range) |
| Supply voltage range | 20 V AC ... 28 V AC |
| | 12 V DC ... 32 V DC |
| Typical current consumption | typ. 114 mA |

General

| | |
|------------------|--------------|
| Mounting type | DIN rail |
| Type AX | Block design |
| Net weight | 277 g |
| Housing material | Aluminum |

Standards and Regulations

| | |
|---------------------------------|--|
| Electromagnetic compatibility | Conformance with EMC Directive 2004/108/EC |
| Developed in acc. with standard | IEC 61000-6.2 |
| Test standard | IEC 61000-4-2 (ESD) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-3 (immunity to radiated interference) |
| Test result | Criterion A |
| Test standard | IEC 61000-4-4 (burst) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-5 (surge) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-6 (immunity to conducted interference) |

Industrial Ethernet Switch - FL SWITCH SFN 5TX-24VAC - 2891021

Technical data

Standards and Regulations

| | |
|---|---|
| Test result | Criterion A |
| Test standard | IEC 61000-4-8 (immunity to magnetic fields) |
| Test result | Criterion A |
| Test standard | EN 55022 (emitted interference) |
| Test result | Criterion A |
| Test section | 500 V DC 1 min. |
| Noise emission | EN 61000-6-4 |
| Noise immunity | EN 61000-6-2:2005 |
| Vibration (storage/transport) | 5g, 150 Hz, in acc. with IEC 60068-2-6 |
| Free from substances that could impair the application of coating | In acc. with VW specification |
| Vibration (operation) | In acc. with IEC 60068-2-6: 5g, 150 Hz |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250501 |
| eCl@ss 4.1 | 27250501 |
| eCl@ss 5.0 | 19030117 |
| eCl@ss 5.1 | 19030117 |
| eCl@ss 6.0 | 19170106 |
| eCl@ss 7.0 | 19170106 |
| eCl@ss 8.0 | 19170106 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000734 |
| ETIM 3.0 | EC000734 |
| ETIM 4.0 | EC000734 |
| ETIM 5.0 | EC000734 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172901 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201410 |
| UNSPSC 13.2 | 43201410 |

Approvals

Approvals

Industrial Ethernet Switch - FL SWITCH SFN 5TX-24VAC - 2891021

Approvals

Approvals

UL Listed / cUL Listed / EAC / EAC / cULus Listed

Ex Approvals

UL Listed / cUL Listed / cULus Listed

Approvals submitted

Approval details

UL Listed 

cUL Listed 

EAC

EAC

cULus Listed 

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|--|---------|-------------------------|----------------------------|
| Ethernet switch, 5 TP RJ45 ports, automatic detection of data transmission speed of 10 or 100 Mbps (RJ45), autocrossing function | 2891021 | FL SWITCH SFN 5TX-24VAC | Buy on EAN |