



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

# Antenna cable - RAD-PIG-RSMA/N-3 - 2903266

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Antenna cable, 3 m in length; N (male) -> RSMA (male), impedance 50 ohms



The illustration shows a version of the product

## Product Description

Coaxial antenna adapter cable, N (male) to RSMA (male), 50 Ω, 3.0 m

## Key Commercial Data

|              |   |
|--------------|---|
| Packing unit | 1 STK   |
| GTIN         | <br>4 046356 743464 |

## Technical data

### Dimensions

|                    |         |
|--------------------|---------|
| Fixed cable length | 3 m     |
| External diameter  | 4.95 mm |

### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 85 °C |
|---------------------------------|------------------|

### General

|                        |             |
|------------------------|-------------|
| Connection method      | RSMA (male) |
|                        | N (male)    |
| Cable type             | 195         |
| Minimum bending radius | 12.70 mm    |
| Frequency range        | 900 MHz     |
|                        | 2.4 GHz     |
|                        | 5 GHz       |
| Impedance              | 50 Ω        |

### Attenuation

|               |         |
|---------------|---------|
| 868 / 900 MHz | 1.2 dB  |
| 2.4 GHz       | 1.95 dB |
| 5 GHz         | 2.95 dB |

# Antenna cable - RAD-PIG-RSMA/N-3 - 2903266

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27230207 |
| eCl@ss 4.1 | 27250312 |
| eCl@ss 5.0 | 27242208 |
| eCl@ss 5.1 | 27061802 |
| eCl@ss 6.0 | 27242208 |
| eCl@ss 7.0 | 27242208 |
| eCl@ss 8.0 | 27060310 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001423 |
| ETIM 4.0 | EC000019 |
| ETIM 5.0 | EC001682 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211506 |
| UNSPSC 7.0901 | 43223108 |
| UNSPSC 11     | 39121008 |
| UNSPSC 12.01  | 43223108 |
| UNSPSC 13.2   | 43223108 |

## Approvals

### Approvals

---

Approvals

EAC / EAC

---

Ex Approvals

---

Approvals submitted

---

### Approval details

|     |
|-----|
| EAC |
|-----|

|     |
|-----|
| EAC |
|-----|

---

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product  | Code    | Reference            | Product link               |
|--|---------|----------------------|----------------------------|
| Antenna cable, 3 m in length; N (male) -> RSMA (male), impedance 50 ohms | 2903266 | RAD-PIG-RSMA/<br>N-3 | <a href="#">Buy on EAN</a> |