



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Single relay - REL-IR4/L-230AC/4X21 - 2903688

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in industrial relay with power contacts, 4 PDTs, test key, status LED, mechanical switch position indicator, input voltage: 230 V AC

The figure shows version REL-IR4/LDP- 24DC/4X21

Key Commercial Data

| | |
|------------------------|---------------------|
| Packing unit | 10 STK |
| Minimum order quantity | 10 STK |
| GTIN | 4 046356 759014 |

Technical data

Dimensions

| | |
|--------|---------|
| Width | 21.2 mm |
| Height | 35.6 mm |
| Depth | 27.5 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -40 °C ... 55 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

Coil side

| | |
|---|--|
| Nominal input voltage U_N | 230 V AC |
| Input voltage range in reference to U_N | see diagram |
| Typical input current at U_N | 6.5 mA |
| Typical response time | 5 ms ... 15 ms (depending on phase relation) |
| Typical release time range | 5 ms ... 20 ms (depending on phase relation) |
| Status display | Yellow LED |

Contact side

| | |
|---------------------------|----------------|
| Contact type | 4 PDTs |
| Contact material | AgNi |
| Maximum switching voltage | 250 V AC/DC |
| Minimum switching voltage | 5 V (At 24 mA) |

Single relay - REL-IR4/L-230AC/4X21 - 2903688

Technical data

Contact side

| | |
|--|---------------------------|
| Min. switching current | 5 mA (at 24 V) |
| Maximum inrush current | 16 A (20 ms, N/O contact) |
| Limiting continuous current | 6 A |
| Interrupting rating (ohmic load) max. | 144 W (at 24 V DC) |
| | 124 W (at 48 V DC) |
| | 108 W (at 60 V DC) |
| | 52 W (at 110 V DC) |
| | 48 W (at 220 V DC) |
| | 1500 VA (for 250 V AC) |
| Switching capacity min. | 0.12 W |
| Switching capacity in acc. with DIN VDE 0660/IEC 60947 | 2 A (at 24 V, DC13) |
| | 0.22 A (at 120 V, DC13) |
| | 0.11 A (at 250 V, DC13) |
| | 1.5 A (at 24 V, AC15) |
| | 1.5 A (at 120 V, AC15) |
| | 1 A (at 240 V, AC15) |

General

| | |
|--|--|
| Test voltage relay winding/relay contact | 2.5 kV _{rms} (50 Hz, 1 min.) |
| Test voltage PDT/PDT | 2 kV _{rms} (50 Hz, 1 min.) |
| Operating mode | 100% operating factor |
| Degree of protection | RT I |
| Mechanical service life | Approx. 2 x 10 ⁷ cycles |
| Designation | Air clearances and creepage distances between the power circuits |
| Standards/regulations | IEC 60664 |
| Rated insulation voltage | 250 V AC |
| Degree of pollution | 2 |
| Overvoltage category | II |
| Designation | Standards/regulations |
| Standards/regulations | IEC 61810 |
| Mounting position | any |

Standards and Regulations

| | |
|----------------------------------|--|
| Connection in acc. with standard | CSA |
| Designation | Air clearances and creepage distances between the power circuits |
| Standards/regulations | IEC 60664 |
| Rated insulation voltage | 250 V AC |
| Insulation | Basic insulation |
| Degree of pollution | 2 |
| Overvoltage category | II |
| Designation | Standards/regulations |

Single relay - REL-IR4/L-230AC/4X21 - 2903688

Technical data

Standards and Regulations

| | |
|-----------------------|-----------|
| Standards/regulations | IEC 61810 |
|-----------------------|-----------|

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27371104 |
| eCl@ss 4.1 | 27371104 |
| eCl@ss 5.0 | 27371001 |
| eCl@ss 5.1 | 27371001 |
| eCl@ss 6.0 | 27371001 |
| eCl@ss 7.0 | 27371001 |
| eCl@ss 8.0 | 27371601 |
| eCl@ss 9.0 | 27371601 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000196 |
| ETIM 4.0 | EC000196 |
| ETIM 5.0 | EC001437 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211916 |
| UNSPSC 7.0901 | 39121515 |
| UNSPSC 11 | 39121515 |
| UNSPSC 12.01 | 39121515 |
| UNSPSC 13.2 | 39121515 |

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / VDE Zeichengenehmigung / EAC / EAC / cULus Recognized




Ex Approvals

Approvals submitted

Approval details


Single relay - REL-IR4/L-230AC/4X21 - 2903688

Approvals




Drawings

Circuit diagram




Diagram




Operating voltage range

Single relay - REL-IR4/L-230AC/4X21 - 2903688

Diagram




Diagram



Interrupting rating

Electrical service life

Diagram



Service life reduction factor

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
 Flachsmarktstr. 8
 32825 Blomberg
 Germany
 Tel. +49 5235 300
 Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|---|---------|--------------------------|----------------------------|
| Plug-in industrial relay with power contacts, 4 PDTs, test key, status LED, mechanical switch position indicator, input voltage: 230 V AC | 2903688 | REL-IR4/ L-230AC/4X21 | Buy on EAN |