



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Electronic housing - ME 35 UTG GN - 2907208

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Component housing without vents, Lower part, Cross connection: without bus connector, Color: green, Width: 35 mm, Constructional height: 114.5 mm, Number of positions cross connector: not relevant

Why buy this product

- Tool-free mounting
- Low design width with a high number of positions
- Large assembly area
- Same PCB geometry for all design widths
- Recessed labeling areas
- Fast mounting on DIN rails according to EN 60715
- Inflammability class V0 according to UL 94
- Cost savings thanks to easy device production
- Material and part identification embossed on the housing (recyclability)
- Optional BUS connection integrated in the housing, for either parallel or serial contacting
- Metal foot catch
- Functional earth ground contact (EMC) integrated in the housing base
- Electronic components can be partially removed

Key Commercial Data

Packing unit	10 STK
GTIN	 4 017918 131425

Technical data

General

Housing type	Component housing
Housing material	Polyamide
Color	green

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
---------------------------------	--

Dimensions

Length	99 mm
--------	-------

Electronic housing - ME 35 UTG GN - 2907208

Technical data

Dimensions

Constructional height	114.5 mm
Width	35 mm

Technical data

Flammability rating according to UL 94	V0
Power dissipation without gap	7.5 W
Power dissipation with 20 mm gap	13.8 W
Number of positions	24

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Electronic housing - ME 35 UTG GN - 2907208

Approvals

Approvals

UL Recognized


Ex Approvals

Approvals submitted

Approval details




Drawings



Dimensions of the electronic housing ME... with double-level upper part Dimensions of the electronic housing ME... with double-level upper part


Dimensional drawing



Inner housing dimensions, electronic housing ME 35 ...

Electronic housing - ME 35 UTG GN - 2907208

Dimensional drawing



Dimensional drawing of the ME... printed circuit board if the double level upper part is used

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button](#).

Product	Code	Reference	Product link
Component housing without vents, Lower part, Cross connection: without bus connector, Color: green, Width: 35 mm, Constructional height: 114.5 mm, Number of positions cross connector: not relevant	2907208	ME 35 UTG GN	Buy on EAN