



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking HERE. [HERE](#)

Timer relay - ETD-BL-1T-ON-CC-300MIN - 2917447

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Timer relay with switch-on delay (with control contact) and an adjustable time range (3 min - 300 min), with screw connection

The figure shows the ETD-BL-1T-ON-CC- 10S 2917418 version

Product Description

Compact timer relay in 6.2 mm housing for controlling time sequences. The time is set on the front of the device using a labeled thumbwheel, which is recessed to protect against accidental modification. A screwdriver is used to change the settings (blade width 2.5 mm). The compact timer relays are available with different time ranges as well as with a screw, spring-cage, and push-in connection.

Why buy this product

- 6.2 mm narrow design width
- High level of setting accuracy thanks to labeled and illuminated thumb wheel



Key Commercial Data

| | |
|--------------|-------|
| Packing unit | 1 STK |
| GTIN | |

Technical data

Dimensions

| | |
|--------|--------|
| Width | 6.2 mm |
| Height | 80 mm |
| Depth | 86 mm |

Ambient conditions

| | |
|---|--|
| Ambient temperature (operation) | -20 °C ... 65 °C |
| Ambient temperature (storage/transport) | -25 °C ... 80 °C |
| Permissible humidity (operation) | 15 % ... 85 % |
| Noise immunity | EN 61000-6-2 |
| | When being exposed to interference, there may be minimal deviations. |

Timer relay - ETD-BL-1T-ON-CC-300MIN - 2917447

Technical data

Coil side

| | |
|---------------------|--|
| Input voltage range | 24 V DC (19,2 V DC ...30 V DC) |
| Function | ON-CC: With switch-on delay with control contact |
| Time setting range | 3 min. ... 300 min. |

Contact side

| | |
|--------------|-------------------|
| Contact type | 1 floating PDT |
| Output fuse | 6.3 A (fast-blow) |

General

| | |
|----------------------------------|--|
| Status display | Green LED (POWER) Yellow LED (relay active) |
| Mechanical service life | Approx. 2×10^7 cycles |
| Mounting position | any |
| Assembly instructions | on standard DIN rail NS 35 in accordance with EN 60715 |
| Color | green |
| Housing insulation material | Polyamide PA, self-extinguishing |
| Permissible humidity (operation) | 15 % ... 85 % |
| Rated insulation voltage | 300 V AC (According to EN 50178) |
| Conformance | CE-compliant |
| ATEX | # II 3 G Ex nA nC IIC T4 Gc X |
| UL, USA / Canada | UL/C-UL listed UL 508 |
| GL | GL EMC 1 C |

Connection data

| | |
|---------------------------------------|----------------------|
| Conductor cross section flexible min. | 0.14 mm ² |
| Conductor cross section flexible max. | 2.5 mm ² |
| Conductor cross section solid min. | 0.14 mm ² |
| Conductor cross section solid max. | 2.5 mm ² |
| Conductor cross section AWG min. | 30 |
| Conductor cross section AWG max. | 12 |
| Stripping length | 8 mm |
| Connection method | Screw connection |

Control contact

| | |
|----------------------|-------------------------------|
| Connection name | Non-floating, terminals A1-B1 |
| Control pulse length | min. 50 ms |

Standards and Regulations

| | |
|--|--|
| Electromagnetic compatibility | Conformance with EMC Directive 2004/108/EC |
| Noise emission | EN 61000-6-4 |
| Noise immunity | EN 61000-6-2 |
| Flammability rating according to UL 94 | V0 |
| Low Voltage Directive | Conformance with LV directive 2006/95/EC |

Timer relay - ETD-BL-1T-ON-CC-300MIN - 2917447

Technical data

Standards and Regulations

| | |
|------------------|-------------------------------|
| Conformance | CE-compliant |
| ATEX | # II 3 G Ex nA nC IIC T4 Gc X |
| UL, USA / Canada | UL/C-UL listed UL 508 |
| GL | GL EMC 1 C |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27371103 |
| eCl@ss 4.1 | 27371103 |
| eCl@ss 5.0 | 27371701 |
| eCl@ss 5.1 | 27371701 |
| eCl@ss 6.0 | 27371790 |
| eCl@ss 7.0 | 27371790 |
| eCl@ss 8.0 | 27371605 |
| eCl@ss 9.0 | 27371605 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001439 |
| ETIM 3.0 | EC001439 |
| ETIM 4.0 | EC001439 |
| ETIM 5.0 | EC001439 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211920 |
| UNSPSC 7.0901 | 39121519 |
| UNSPSC 11 | 39121519 |
| UNSPSC 12.01 | 39121519 |
| UNSPSC 13.2 | 39121519 |

Approvals

Approvals

Approvals

UL Listed / cUL Listed / GL / GL-SW / EAC / GL / cULus Listed

Ex Approvals

ATEX

Timer relay - ETD-BL-1T-ON-CC-300MIN - 2917447

Approvals

Approvals submitted

Approval details

UL Listed

cUL Listed

GL

GL-SW


EAC

GL

cULus Listed

Drawings

Block diagram



Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|---|---------|------------------------|----------------------------|
| Timer relay with switch-on delay (with control contact) and an adjustable time range (3 min - 300 min), with screw connection | 2917447 | ETD-BL-1T-ON-CC-300MIN | Buy on EAN |