



Automatización Eléctrica
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

Fuse modular terminal block - ZFK 6-DREHSILA 250 (6,3X32) - 3025574

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Spring-cage terminal block-fuse terminal block for cartridge fuse inserts with screw cap, cross section: 0.5 - 6 mm², width: 12 mm, color: black

The illustration shows version ZFK 6-DREHSI 24 (5X20)

Why buy this product

- With fuse screw cap

Key Commercial Data

| | |
|--------------|---------------------|
| Packing unit | 25 STK |
| GTIN | 4 017918 154646 |

Technical data

General

| | |
|--|---|
| Number of levels | 1 |
| Number of connections | 2 |
| Nominal cross section | 6 mm ² |
| Color | black |
| Insulating material | PA |
| Flammability rating according to UL 94 | V0 |
| Fuse | G / 6,3 x 32 |
| Fuse type | Glass / ceramics / ... |
| Rated surge voltage | 6 kV |
| Degree of pollution | 3 |
| Overvoltage category | III |
| Insulating material group | I |
| LED voltage range | 110 V AC/DC ... 250 V AC/DC |
| LED current range | 0.5 mA ... 0.0025 A |
| Connection in acc. with standard | IEC 60947-7-3 |
| Maximum load current | 10 A (if used as disconnect terminal block. With fuse, the current is determined by the fuse used.) |
| Nominal current I _N | 10 A (if used as disconnect terminal block. With fuse, the current is determined by the fuse used.) |

Fuse modular terminal block - ZFK 6-DREHSILA 250 (6,3X32) - 3025574

Technical data

General

| | |
|-----------------------|---|
| Nominal voltage U_N | 800 V (if used as disconnect terminal block. With fuse, the voltage is determined by the light indicator used.) |
| Open side panel | No |

Dimensions

| | |
|------------------|---------|
| Width | 12 mm |
| Length | 86.5 mm |
| Height NS 35/7,5 | 56.5 mm |
| Height NS 35/15 | 64 mm |

Connection data

| | |
|---|------------------------|
| Conductor cross section solid min. | 0.5 mm ² |
| Conductor cross section solid max. | 10 mm ² |
| Conductor cross section flexible min. | 0.5 mm ² |
| Conductor cross section flexible max. | 6 mm ² |
| Conductor cross section AWG min. | 20 |
| Conductor cross section AWG max. | 8 |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.5 mm ² |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 6 mm ² |
| Conductor cross section flexible, with ferrule with plastic sleeve min. | 0.5 mm ² |
| Conductor cross section flexible, with ferrule with plastic sleeve max. | 6 mm ² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm ² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 1.5 mm ² |
| Connection method | Spring-cage connection |
| Stripping length | 12 mm |

Standards and Regulations

| | |
|--|---------------|
| Connection in acc. with standard | CUL |
| | IEC 60947-7-3 |
| Flammability rating according to UL 94 | V0 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27141116 |
| eCl@ss 4.1 | 27141116 |
| eCl@ss 5.0 | 27141116 |
| eCl@ss 5.1 | 27141116 |
| eCl@ss 6.0 | 27141116 |
| eCl@ss 7.0 | 27141116 |
| eCl@ss 8.0 | 27141116 |

Fuse modular terminal block - ZFK 6-DREHSILA 250 (6,3X32) - 3025574

Classifications

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000899 |
| ETIM 3.0 | EC000899 |
| ETIM 4.0 | EC000899 |
| ETIM 5.0 | EC000899 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211825 |
| UNSPSC 7.0901 | 39121422 |
| UNSPSC 11 | 39121422 |
| UNSPSC 12.01 | 39121422 |
| UNSPSC 13.2 | 39121422 |

Approvals

Approvals


Approvals


UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

| | |
|---|-------|
| UL Recognized  | |
| mm ² /AWG/kcmil | 20-8 |
| Nominal current I _N | 20 A |
| Nominal voltage U _N | 600 V |

| | |
|--|------|
| cUL Recognized  | |
| mm ² /AWG/kcmil | 20-8 |
| Nominal current I _N | 20 A |

Fuse modular terminal block - ZFK 6-DREHSILA 250 (6,3X32) - 3025574

Approvals


| | |
|--------------------|-------|
| Nominal voltage UN | 600 V |
|--------------------|-------|

| |
|-----|
| EAC |
|-----|

| |
|---|
| cULus Recognized  US |
|---|

Drawings

Circuit diagram



Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product | Code | Reference | Product link |
|---|---------|-----------------------------|----------------------------|
| Spring-cage terminal block-fuse terminal block for cartridge fuse inserts with screw cap, cross section: 0.5 - 6 mm ² , width: 12 mm, color: black | 3025574 | ZFK 6-DREHSILA 250 (6,3X32) | Buy on EAN |