



**Automatización Eléctrica**  
Especialistas en Automatización

At the end of this document you will find links to products related to this catalog. You can go directly to our shop by clicking [HERE](#). [HERE](#)

## Disconnect terminal block - PT 2,5-TWIN-TGB - 3210193

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Disconnect terminal block, Connection type: Push-in connection, Cross section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, Nominal current: 16 A, Nominal voltage: 400 V, Length: 81.9 mm, Width: 5.2 mm, Color: gray, Assembly: NS 35/7,5, NS 35/15

### Why buy this product

- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- The compact design and front connection enable wiring in a confined space
- In addition to the testing facility in the double function shaft, all terminal blocks provide an additional test connection
- Tested for railway applications

### Key Commercial Data

|              |                     |
|--------------|---------------------|
| Packing unit | 50 STK              |
| GTIN         | <br>4 046356 693967 |

### Technical data

#### General

|  |  |
|--|--|
| Note                                   | The max. load current must not be exceeded by the total current of all connected conductors.<br>Current and voltage are determined by the plug used. |
| Number of levels                       | 1  |
| Number of connections                  | 3  |
| Nominal cross section                  | 2.5 mm <sup>2</sup>  |
| Color                                  | gray   |
| Insulating material                    | PA   |
| Flammability rating according to UL 94 | V0   |
| Area of application                    | Railway industry<br>Mechanical engineering<br>Plant engineering  |
| Rated surge voltage                    | 6 kV   |
| Degree of pollution                    | 3  |
| Overvoltage category                   | III  |
| Insulating material group              | I  |
| Connection in acc. with standard       | IEC 60947-7-1  |

# Disconnect terminal block - PT 2,5-TWIN-TGB - 3210193

## Technical data

### General

|   |   |
|---|---|
| Maximum load current  | 16 A (with 4 mm <sup>2</sup> conductor cross section) |
| Nominal current I <sub>N</sub>  | 16 A  |
| Nominal voltage U <sub>N</sub>  | 400 V   |
| Open side panel   | Yes   |
| Shock protection test specification   | DIN EN 50274 (VDE 0660-514):2002-11                   |
| Back of the hand protection   | guaranteed  |
| Finger protection   | guaranteed  |
| Result of surge voltage test  | Test passed   |
| Surge voltage test setpoint   | 7.3 kV  |
| Result of power-frequency withstand voltage test  | Test passed   |
| Power frequency withstand voltage setpoint  | 1.89 kV   |
| Result of the test for mechanical stability of terminal points (5 x conductor connection) | Test passed   |
| Result of bending test  | Test passed   |
| Bending test rotation speed   | 10 rpm  |
| Bending test turns  | 135   |
| Bending test conductor cross section/weight   | 0.14 mm <sup>2</sup> / 0.2 kg                         |
|   | 2.5 mm <sup>2</sup> / 0.7 kg                          |
|   | 4 mm <sup>2</sup> / 0.9 kg                            |
| Tensile test result   | Test passed   |
| Conductor cross section tensile test  | 0.14 mm <sup>2</sup>                                  |
| Tractive force setpoint   | 10 N  |
| Conductor cross section tensile test  | 2.5 mm <sup>2</sup>                                   |
| Tractive force setpoint   | 50 N  |
| Conductor cross section tensile test  | 4 mm <sup>2</sup>                                     |
| Tractive force setpoint   | 60 N  |
| Result of tight fit on support  | Test passed   |
| Tight fit on carrier  | NS 35   |
| Setpoint  | 1 N   |
| Result of voltage-drop test   | Test passed   |
| Result of temperature-rise test   | Test passed   |
| Short circuit stability result  | Test passed   |
| Conductor cross section short circuit testing   | 2.5 mm <sup>2</sup>                                   |
| Short-time current  | 0.3 kA  |
| Result of aging test  | Test passed   |
| Ageing test for screwless modular terminal block temperature cycles                       | 192   |
| Result of thermal test  | Test passed   |
| Proof of thermal characteristics (needle flame) effective duration                        | 30 s  |
| Oscillation, broadband noise test result  | Test passed   |
| Test specification, oscillation, broadband noise  | DIN EN 50155 (VDE 0115-200):2008-03                   |
| Test spectrum   | Service life test category 2, bogie mounted           |

# Disconnect terminal block - PT 2,5-TWIN-TGB - 3210193

## Technical data

### General

|   |  |
|---|--|
| Test frequency  | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level   | $6.12 \text{ (m/s}^2\text{)}^2\text{/Hz}$      |
| Acceleration  | 3.12 g   |
| Test duration per axis  | 5 h  |
| Test directions   | X-, Y- and Z-axis                              |
| Shock test result   | Test passed                                    |
| Test specification, shock test  | DIN EN 50155 (VDE 0115-200):2008-03            |
| Shock form  | Half-sine                                      |
| Acceleration  | 30g  |
| Shock duration  | 18 ms  |
| Number of shocks per direction  | 3  |
| Test directions   | X-, Y- and Z-axis (pos. and neg.)              |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C   |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C   |
| Static insulating material application in cold                          | -60 °C   |

### Dimensions

|                  |          |
|------------------|----------|
| Width            | 5.2 mm   |
| End cover width  | 2.2 mm   |
| Length           | 81.9 mm  |
| Height           | 35.20 mm |
| Height NS 35/7,5 | 36.7 mm  |
| Height NS 35/15  | 44.2 mm  |

### Connection data

|   |                      |
|---|----------------------|
| Connection method   | Push-in connection   |
| Connection in acc. with standard  | IEC 60947-7-1        |
| Conductor cross section solid min.  | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.  | 4 mm <sup>2</sup>    |
| Conductor cross section AWG min.  | 26                   |
| Conductor cross section AWG max.  | 12                   |
| Conductor cross section flexible min.   | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.   | 2.5 mm <sup>2</sup>  |
| Min. AWG conductor cross section, flexible  | 26                   |
| Max. AWG conductor cross section, flexible  | 14                   |
| Conductor cross section flexible, with ferrule without plastic sleeve min.              | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max.              | 2.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.                 | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.                 | 2.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm <sup>2</sup>  |

# Disconnect terminal block - PT 2,5-TWIN-TGB - 3210193

## Technical data

### Connection data

|                           |                |
|---------------------------|----------------|
| Stripping length          | 8 mm ... 10 mm |
| Internal cylindrical gage | A3             |

### Standards and Regulations

|  |               |
|--|---------------|
| Connection in acc. with standard       | CSA           |
|  | IEC 60947-7-1 |
| Flammability rating according to UL 94 | V0            |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141126 |
| eCl@ss 4.1 | 27141126 |
| eCl@ss 5.0 | 27141126 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141126 |

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000902 |
| ETIM 4.0 | EC000902 |
| ETIM 5.0 | EC000902 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / VDE Zeichengenehmigung / IEC EE CB Scheme / CSA / GL / BV / LR / EAC / cULus Recognized

---

#### Ex Approvals

---

# Disconnect terminal block - PT 2,5-TWIN-TGB - 3210193

## Approvals

Approvals submitted

### Approval details

UL Recognized

|                                | B     | C     | D     |
|--------------------------------|-------|-------|-------|
| mm <sup>2</sup> /AWG/kcmil     | 26-12 | 26-12 | 26-12 |
| Nominal current I <sub>N</sub> | 16 A  | 16 A  | 5 A   |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V | 600 V |

cUL Recognized

|                                | B     | C     | D     |
|--------------------------------|-------|-------|-------|
| mm <sup>2</sup> /AWG/kcmil     | 26-12 | 26-12 | 26-12 |
| Nominal current I <sub>N</sub> | 16 A  | 16 A  | 5 A   |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V | 600 V |

VDE Zeichengenehmigung

| mm <sup>2</sup> /AWG/kcmil     | 0.2-2.5 |
|--------------------------------|---------|
| Nominal current I <sub>N</sub> | 16 A    |
| Nominal voltage U <sub>N</sub> | 400 V   |

IECEE CB Scheme

| mm <sup>2</sup> /AWG/kcmil     | 2.5   |
|--------------------------------|-------|
| Nominal current I <sub>N</sub> | 16 A  |
| Nominal voltage U <sub>N</sub> | 400 V |

CSA

|                                | B     | C     | D     |
|--------------------------------|-------|-------|-------|
| mm <sup>2</sup> /AWG/kcmil     | 26-12 | 26-12 | 26-12 |
| Nominal current I <sub>N</sub> | 16 A  | 16 A  | 5 A   |

# Disconnect terminal block - PT 2,5-TWIN-TGB - 3210193

## Approvals


|                    | B     | C     | D     |
|--------------------|-------|-------|-------|
| Nominal voltage UN | 300 V | 300 V | 600 V |

GL

BV

LR

EAC

cULus Recognized 

## Drawings

Circuit diagram



Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



Below is a list of articles with direct links to our shop Electric Automation Network where you can see:

- Quote per purchase volume in real time.
- Online documentation and datasheets of all products.
- Estimated delivery time enquiry in real time.
- Logistics systems for the shipment of materials almost anywhere in the world.
- Purchasing management, order record and tracking of shipments.

To access the product, [click on the green button.](#)

| Product   | Code    | Reference       | Product link               |
|---|---------|-----------------|----------------------------|
| Disconnect terminal block, Connection type: Push-in connection, Cross section: 0.14 mm <sup>2</sup> - 4 mm <sup>2</sup> , AWG: 26 - 12, Nominal current: 16 A, Nominal voltage: 400 V, Length: 81.9 mm, Width: 5.2 mm, Color: gray, Assembly: NS 35/7,5, NS 35/15 | 3210193 | PT 2,5-TWIN-TGB | <a href="#">Buy on EAN</a> |